

# A very unkind style guide for technical writers

YI Hoze

March 3, 2010

## Contents

<b>1</b>	<b>Style</b>	<b>1</b>
1.1	hoze-layout.sty . . . . .	1
1.2	hoze-illust.sty . . . . .	3
1.2.1	To place a figure or a picture . . . . .	3
1.2.2	To illustrate a figure or a picture in a row . . . . .	4
1.2.3	To place a table . . . . .	6
1.2.4	To illust a table in a row . . . . .	7
1.3	hoze-misc.sty . . . . .	11
1.3.1	Thumb index and watermark . . . . .	11
1.3.2	To index a term . . . . .	12
1.3.3	To index all entries of a list . . . . .	12
1.3.4	To decorate letters and paragraphs . . . . .	14
1.3.5	Sectional division . . . . .	15
<b>A</b>	<b>Style Package Source</b>	<b>17</b>
A.1	hoze-layout.sty . . . . .	17
A.2	hoze-illust.sty . . . . .	22
A.3	hoze-misc.sty . . . . .	42

## List of Figures

1.1	At the seashore . . . . .	4
1.2	An example of tikz picture . . . . .	4
1.3	A Hierarchical structure . . . . .	6

# Chapter 1

## Style

### 1.1 hoze-layout.sty

```
\ifvartwo
\ifvartwoexpand \ifvartwoexpand{\marginparwidth}{\tableofcontents}
\setlayout
\normallayout
\vartwolayout
\normalmargin
\vartwomargin
\normalfolio
\vartwofolio
\sethffont
\ebooksize
\pbooksize
\ifebook

A4
A4landscape
A3landscape
paperwidth
paperheight
stockwidth
stockheight
ebook
layout
```

#### **Example**

```
\setkeys{layout}{paperheight=297mm, paperwidth=210mm, stockheight=353mm, %
stockwidth=250mm}
```

```
\ebooksize  
\pbooksize  
\normallayout  
\vartwolayout
```

## 1.2 hoze-illust.sty

```
\settabcaptionstyle
\setfigcaptionstyle
\setfigjustify
\setfigscale
\restorefigscale
\excludegraphics
```

### 1.2.1 To place a figure or a picture

```
\placefig      is short for \placefigure.
\placefigure   \placefigure[float=false, caption={blah blah}]{file}
\setplacefigure
```

Options for the `\placefigure` command are:

```
float          =true / false (default)
type           = figure (default) / picture
caption
captionfont
captionstyle
label
figurejustify
topspace
bottomspace
rotate        =90 (default)
scale
```

#### **Example**

```
\setplacefigure{
  float=false,
  type=figure,
  captionfont=\rmfamily\small\bfseries,
  rotate=0
}
```

#### **Example**

```
\placefigure[float=false, caption={At the seashore}, captionstyle=\raggedright, %
  figurejustify=\centering, scale=0.9, rotate=-45]{Silver}
```



### Example

```
\placefigure[type=picture, caption={An example of tikz picture}]{
  \begin{tikzpicture}
  \node {root}
  child {node {left}}
  child {node {right}}
  child {node {child}}
  child {node {child}}
  };
\end{tikzpicture}
}
```




Figure 1.2: An example of tikz picture

### 1.2.2 To illustrate a figure or a picture in a row

`\illustfig` is short for `\illustfigure`.

```
\illustfigure \illustfigure[caption={blah blah}]{file}{text}
```

```
\setillustfigure
```

Options for the `\illustfigure` command are:

`type` = figure (default) / picture

`caption`

`captionfont`

`captionstyle`

```

label
textstyle
figureposition =left / right
figurewidth
figurejustify
scale
protrude      =true (default) / false
protrudlength
frame
framerule
framesep
align         =top / middle / bottom
list
topspace
bottomspace

```

**Example**

```

\setillustfigure{
  captionfont=\rmfamily\small\bfseries,
  textstyle=\sloppy,
  figureposition=left,
  frame=false,
  align=top,
  type=figure
}

```

**Example**

```

\illustfigure[figureposition=right, frame, framerule=0.5pt, framesep=5pt, scale=1.2, %
  align=middle, textstyle=\sloppy\raggedleft]{Silver}{
  Silver is Hoze's only son, who is in the fourth grade of primary school.
}

```


Silver is Hoze's only son, who is in the fourth grade of primary school.

**Example**

```

\illustfigure[type=picture, figurewidth=7.5cm, figurejustify=\raggedleft, caption={A %
    Hierarchical structure}, captionstyle=\raggedright]{
  \begin{tikzpicture}
  \node {root} [grow'=up]
  child {node {left}}
  child {node {right}}
  child {node {child}}
  child {node {child}}
  };
\end{tikzpicture}
}{
Admittedly, in reality trees are more likely to grow upward and not downward as %
    above. You can tell
whether the author of a paper is a mathematician or a computer scientist by %
    looking at the direction their
trees grow. A computer scientist's trees will grow downward while a %
    mathematician's tree will grow upward.
}

```



Admittedly, in reality trees are more likely to grow upward and not downward as above. You can tell whether the author of a paper is a mathematician or a computer scientist by looking at the direction their trees grow. A computer scientist's trees will grow downward while a mathematician's tree will grow upward.

Figure 1.3: A Hierarchical structure

### 1.2.3 To place a table

```

\placetable \placetable[caption={blah blah}]{\begin{tabular}...\end{tabular}}
\setplacetable

```

Options for the `\placetable` command are:

```

float
caption
captionfont
captionstyle
label
tabularfont
tabularstyle
topspace
bottomspace

```

#### **Example**

```
\setplacetable{
  float=false,
  captionfont=\rmfamily\small\bfseries,
  tabularfont=\sffamily\small
}
```

**Example**

```
\placetable[float=false, caption={International Standard Paper sizes}, %
  tabularfont=\sffamily\small]{
  \begin{tabular}{ccccc}
  \toprule
  & \textbf{A} & \textbf{B} & \textbf{C} & \textbf{JIS B} \\
  \midrule
  0 & 841x1189 & 1000x1414 & 917x1297 & 1030x1456 \\
  1 & 594x841 & 707x1000 & 648x917 & 728x1030 \\
  2 & 420x594 & 500x707 & 458x648 & 515x728 \\
  3 & 297x420 & 353x500 & 324x458 & 364x515 \\
  4 & 210x297 & 250x353 & 229x324 & 257x364 \\
  5 & 148x210 & 176x250 & 162x229 & 182x257 \\
  6 & 105x148 & 125x176 & 114x162 & 128x182 \\
  7 & 74x105 & 88x125 & 81x114 & 91x128 \\
  \bottomrule
  \end{tabular}
}
```

**Table 1.1: International Standard Paper sizes**

	<b>A</b>	<b>B</b>	<b>C</b>	<b>JIS B</b>
0	841x1189	1000x1414	917x1297	1030x1456
1	594x841	707x1000	648x917	728x1030
2	420x594	500x707	458x648	515x728
3	297x420	353x500	324x458	364x515
4	210x297	250x353	229x324	257x364
5	148x210	176x250	162x229	182x257
6	105x148	125x176	114x162	128x182
7	74x105	88x125	81x114	91x128

**1.2.4 To illust a table in a row**

```
\illusttable \illusttable[caption={blah blah}]{\begin{tabular}...\end{tabular}}{text}
\setillusttable
```

Options for the `\illusttable` command are:

```
caption
captionfont
captionstyle
```

label  
tabularfont  
tabularstyle  
tableposition =left / right  
tablewidth  
tablejustify  
textstyle  
protrude =true(default) / false  
protrudelength  
align =top / middle / bottom  
topspace  
bottomspace

**Example**

```
\setillusttable{
  captionfont=\rmfamily\small\bfseries,
  tabularfont=\sfamily\small,
  textstyle=\sloppy,
  tableposition=left
}
```

**Example**

```
\illusttable[align=bottom]{
  \begin{tabular}{c|cc}
  \toprule
  & raster & vector \\
  \midrule
  eps & 0 & 0 \\
  pdf & 0 & 0 \\
  bmp & 0 & X \\
  jpg & 0 & X \\
  png & 0 & X \\
  \bottomrule
  \end{tabular}
}
```

In computer graphics, a raster graphics image or bitmap is a data structure %  
representing a generally rectangular grid of pixels, or points of color, %  
viewable via a monitor, paper, or other display medium. Raster images are %  
stored in image files with varying formats.

```
}
```

	raster	vector
eps	O	O
pdf	O	O
bmp	O	X
jpg	O	X
png	O	X

In computer graphics, a raster graphics image or bitmap is a data structure representing a generally rectangular grid of pixels, or points of color, viewable via a monitor, paper, or other display medium. Raster images are stored in image files with varying formats.

### Example

```
\illusttable[align=top, tabularfont=\tiny, textstyle=\scriptsize]{
  \startgrayrow
  \begin{tabular}{ccccc}
  \toprule
  & \textbf{A} & \textbf{B} & \textbf{C} & \textbf{JIS B} \\
  \midrule
  \grayrow 0 & 841x1189 & 1000x1414 & 917x1297 & 1030x1456 \\
  \grayrow 1 & 594x841 & 707x1000 & 648x917 & 728x1030 \\
  \grayrow 2 & 420x594 & 500x707 & 458x648 & 515x728 \\
  \grayrow 3 & 297x420 & 353x500 & 324x458 & 364x515 \\
  \grayrow 4 & 210x297 & 250x353 & 229x324 & 257x364 \\
  \grayrow 5 & 148x210 & 176x250 & 162x229 & 182x257 \\
  \grayrow 6 & 105x148 & 125x176 & 114x162 & 128x182 \\
  \grayrow 7 & 74x105 & 88x125 & 81x114 & 91x128 \\
  \bottomrule
  \end{tabular}
}{
  \newcounter{mycnt}
  \setcounter{mycnt}{-1}
  \newcommand{\myno}{\stepcounter{mycnt}\themycnt}
  \setgrayrowhook{\myno}
  \startwhiterow
  \begin{tabular}{ccccc}
  \toprule
  & \textbf{A} & \textbf{B} & \textbf{C} & \textbf{JIS B} \\
  \midrule
  \grayrow & 841x1189 & 1000x1414 & 917x1297 & 1030x1456 \\
  \grayrow & 594x841 & 707x1000 & 648x917 & 728x1030 \\
  \grayrow & 420x594 & 500x707 & 458x648 & 515x728 \\
  \grayrow & 297x420 & 353x500 & 324x458 & 364x515 \\
  \grayrow & 210x297 & 250x353 & 229x324 & 257x364 \\
  \grayrow & 148x210 & 176x250 & 162x229 & 182x257 \\
  \grayrow & 105x148 & 125x176 & 114x162 & 128x182 \\
  \grayrow & 74x105 & 88x125 & 81x114 & 91x128 \\
  \bottomrule
  \end{tabular}
}
```

	A	B	C	JIS B
0	841x1189	1000x1414	917x1297	1030x1456
1	594x841	707x1000	648x917	728x1030
2	420x594	500x707	458x648	515x728
3	297x420	353x500	324x458	364x515
4	210x297	250x353	229x324	257x364
5	148x210	176x250	162x229	182x257
6	105x148	125x176	114x162	128x182
7	74x105	88x125	81x114	91x128

	A	B	C	JIS B
0	841x1189	1000x1414	917x1297	1030x1456
1	594x841	707x1000	648x917	728x1030
2	420x594	500x707	458x648	515x728
3	297x420	353x500	324x458	364x515
4	210x297	250x353	229x324	257x364
5	148x210	176x250	162x229	182x257
6	105x148	125x176	114x162	128x182
7	74x105	88x125	81x114	91x128

### 1.3 hoze-misc.sty

Options for the style group are:

chaptertab

paragraph = indent / boundary (default)

#### 1.3.1 Thumb index and watermark

`\chaptertab`

`\setchaptertab`

`\watermark`

`\setwatermark`

`\clearwatermark`

Options for the `\chaptertab` command are:

x

y

width

yspace

color

font

on

off

#### **Example**

```
\setchaptertab{
  x=200,
  y=210,
  width=12,
  height=8,
  yspace=-10,
  color=black,
  font=\LARGE\sffamily\bfseries,
  on
}
```

Options for the `\watermark` command are:

x

y

text

font

fontsize

color

angle

figure

scale

### Example

```
\watermark{x=50, y=50, angle=60, fontsize=90, color=yellow, text={Hoze is so hot!}}
```

### Example

```
\clearwatermark
```

```
\watermark{x=150, y=150, scale=1, angle=-45, figure=MartinLutherKing}
```

### NOTE

You can't make a thumb index and a watermark at the same time. To be precise, the watermark will be vanished by the thumb index when a new chapter begins.

## 1.3.2 To index a term

`\term` puts the argument in the index.

`\termf` typesets the argument in a specified typeface (default is italics) and puts it in the index.

`\termf*` does not index.

`\ui*` typesets the argument in a specified typeface (default is sans-serif) and puts it in the index.

`\ui` does not index.

`\btn` is short for `\button`.

`\button*` typesets the argument in a specified typeface (default is sans-serif) in oval box and puts it in the index.

`\button` does not index.

`\submenu` typesets the arguments with insertions of '>' between each argument and puts the last argument in the index.

### Example

```
\btn{OK}
```

```
\submenu{Installation}{Network Setting}\
```

```
\submenu[Installation]{Network Setting}{IP Setting}\
```

```
\submenu[Installation][Network Setting]{IP Setting}{Profile}
```

Ⓚ Installation > Network Setting

Installation > Network Setting > IP Setting

Installation > Network Setting > IP Setting > Profile

## 1.3.3 To index all entries of a list

`terms` is a list environment, which can put each item's label in the index.

`cmds` is a list environment where you can put a TeX command in item label.

Options for the `terms` environment are:

`index`            =true (default) / false  
`highindex`  
`enumerate`  
`enumeratelabel`  
`base`             is short for labelbase.  
`labelbase`  
`labelfont`  
`marker`  
`markerspace`  
`labelspace`  
`labeloffset`  
`font`  
`justify`  
`iteminterval`

**Example**

```

\begin{terms}[base=ko.TeX Live 2009]\firmlist
  \item[ko.TeX Live 2009] \url{http://faq.ktug.or.kr/faq/KoTeXLive}
  \item[EmEditor] \url{http://www.emeditor.com/}
  \item[Sumatra PDF] \url{http://blog.kowalczyk.info/software/sumatrapdf/index.html}
  \item[pdftk] \url{http://www.accesspdf.com/pdftk/}
\end{terms}

ko.TeX Live 2009 http://faq.ktug.or.kr/faq/KoTeXLive
EmEditor           http://www.emeditor.com/
Sumatra PDF        http://blog.kowalczyk.info/software/sumatrapdf/index.html
pdftk              http://www.accesspdf.com/pdftk/

```

Hoze's so hot!

### 1.3.4 To decorate letters and paragraphs

```
\cirnum
\ovalnum
\recnum
\wrapnum
\setwrapnum
\wrapchar
\alert
\setalert
```

#### Example

```
\setwrapnum{type=circle,base=99}
  \cirnum{10}
  \ovalnum{11}
  \recnum{12}
  \wrapnum{13}
  \wrapchar[type=circle,color=white]{14}
  \wrapchar[type=circle,color=black]{15}
  \wrapchar[type=oval,color=white]{16}
  \wrapchar[type=oval,color=black]{17}
  \wrapchar[type=rectangle,color=white]{18}
  \wrapchar[type=rectangle,color=black]{19}
```

10 11 12 13 14 15 16 17 18 19


Options for the `\alert` command are:

```
frameseparate
labelposition
labelfont
justify
font
```

#### Example

```
\setalert{
  frameseparate=0.5em,
  labelposition=left,
  label=NOTE,
  labelfont=\bfseries,
  justify=\sloppy
}
```

#### Example



```
\alert[label=CAUTION, labelfont=\sffamily]{  
  You can't make a thumb index and a watermark at the same time.  
  To be precise, the watermark will be vanished by the thumb index when a new %  
  chapter begins.  
}
```

**CAUTION**

You can't make a thumb index and a watermark at the same time. To be precise, the watermark will be vanished by the thumb index when a new chapter begins.


**1.3.5 Sectional division**

`\secnewpageon` makes every section begin on a new page from the 2nd section on.

`\secnewpageoff` deactivates `\secnewpageon`.

`\subsecnewpageon` makes every section begin on a new page from the 2nd subsection on.

`\subsecnewpageoff` deactivates `\subsecnewpageon`.





# Appendix A

## Style Package Source

### A.1 hoze-layout.sty

```
1 \ProvidesPackage{hoze-layout}[2010/02/01 v1.00 Page layout for technical writing]
2
3 \RequirePackage{xifthen}
4 \RequirePackage{calc}
5 \RequirePackage{xkeyval}
6 %\RequirePackage{kvoptions}
7
8 %for variant two-column layout
9 \ifthenelse{\isnamedefined{if@vartwo}}{
10     %\setboolean{@vartwo}{true}
11 }{
12     \newboolean{@vartwo}
13     \setboolean{@vartwo}{false}
14 }
15
16 \newcommand\ifvartwo[2]{\if@vartwo#1\else#2\fi}
17 \newcommand\ifvartwoexpand[2]{\ifvartwo{\vartwoexpand{#1}{#2}}{#2}}
18 \newcommand{\vartwoexpand}[2]{
19 \begin{adjustwidth}{-#1}{0pt}%
20 #2%
21 \end{adjustwidth}%
22 }%\marginparwidth, \vartwosecindent
23
24 \ifthenelse{\isnamedefined{foliomarks}}{ }{
25     \newcommand\foliomarks{}
26 }% defined in hoze-misc.sty
27
28 \newif\if@nonelayout\@nonelayoutfalse
29
30 % LAYOUT * * * * *
31
32 \newcommand\trimcentering{
33 \setlength\trimtop{\stockheight}
34 \addtolength\trimtop{-\paperheight}
35 \setlength\trimedge{\stockwidth}
```



```
36 \addtolength\trimedge{-\paperwidth}
37 \settrims{.5\trimtop}{.5\trimedge}
38 }
39
40 \newcommand\normalmargin{%
41 \trimcentering
42 \setulmarginsandblock{.09\paperheight}{.12\paperheight}{*}
43 \setheadfoot{.05\paperheight}{.05\paperheight}
44 \setlrmarginsandblock{.15\paperwidth}{.15\paperwidth}{*}
45 \checkandfixthelayout
46 }
47
48 \newcommand\vartwomargin{%
49 \trimcentering
50 \setulmarginsandblock{.115\paperheight}{.11\paperheight}{*}
51 \setlrmarginsandblock{.3\paperwidth}{.125\paperwidth}{*}
52 \setheadfoot{.045\paperheight}{.045\paperheight}
53 \setmarginnotes{.05\paperwidth}{.125\paperwidth}{Opt}
54 \checkandfixthelayout
55 \let\evensidemargin\oddsidemargin
56 }
57
58 \newcommand\hffont{\rmfamily\bfseries\small}
59 \newcommand\sethffont[1]{\renewcommand\hffont{#1}}
60
61 % normal pagestyle
62 \copypagestyle{normal}{headings}
63 \makepsmarks{normal}{\foliomarks}
64 \makeevenfoot{normal}{\hffont\thepage\quad\leftmark}{\{}}
65 \makeoddfoot{normal}{\{}}{\hffont\rightmark\quad\thepage}
66 \makeevenhead{normal}{\{}}{\{}}
67 \makeoddhead{normal}{\{}}{\{}}
68 \makeheadrule{normal}{\headwidth}{Opt}
69
70 \newcommand\normalfolio{
71 \pagestyle{normal}
72 }
73
74 %\newcommand\pagevrule{~\rule{1.5pt}{7pt}~}
75 %\newcommand\pageno{\wrapchar[type=rectangular,color=black,font=\hffont]{\thepage}}
76
77 % vartwo pagestyle
78 \copypagestyle{vartwo}{companion}
79 \makerunningwidth{vartwo}{\headwidth}
80 \makeheadrule{vartwo}{\headwidth}{\normalrulethickness}
81 \makepsmarks{vartwo}{\foliomarks}
82 \makeheadposition{vartwo}{flushright}{flushright}{flushright}{flushright}
83 \makeevenhead{vartwo}{\hffont\thepage\quad\leftmark}{\{}}
84 \makeoddhead{vartwo}{\{}}{\hffont\rightmark\quad\thepage}
85 \makeevenfoot{vartwo}{\{}}{\{}}
```

```

86 \makeoddfoot{vartwo}{-}{-}
87 \newlength\vartwosecindent
88
89 \newcommand\vartwofolio{
90 \setlength\vartwosecindent{\marginparwidth}
91 \addtolength\vartwosecindent{\marginparsep}
92 \setlength{\headwidth}{\textwidth}
93 \addtolength{\headwidth}{\vartwosecindent}
94 \setsecindent{-\vartwosecindent}
95 \setsubsecindent{-\vartwosecindent}
96 \setsubsubsecindent{-\vartwosecindent}
97 \pagestyle{vartwo}
98 }
99
100 % Page size must be designated as a package option such as paperheight=297mm, %
    paperwidth=210mm, stockheight=353mm, stockwidth=250mm
101 \setlength\paperheight{200mm}
102 \setlength\paperwidth{150mm}
103 \setlength\stockheight{250mm}
104 \setlength\stockwidth{176mm}
105
106 \define@boolkey{layout}{A4}[true]{
107     \setlength\paperheight{297mm}
108     \setlength\paperwidth{210mm}
109     \setlength\stockheight{353mm}
110     \setlength\stockwidth{250mm}
111 }
112
113 \define@boolkey{layout}{A4landscape}[true]{
114     \setlength\paperheight{210mm}
115     \setlength\paperwidth{297mm}
116     \setlength\stockheight{250mm}
117     \setlength\stockwidth{353mm}
118 }
119
120 \define@boolkey{layout}{A3landscape}[true]{
121     \setlength\paperheight{297mm}
122     \setlength\paperwidth{420mm}
123     \setlength\stockheight{353mm}
124     \setlength\stockwidth{500mm}
125 }
126
127 \define@key{layout}{paperheight}{\setlength\paperheight{#1}}
128 \define@key{layout}{paperwidth}{\setlength\paperwidth{#1}}
129 \define@key{layout}{stockheight}{\setlength\stockheight{#1}}
130 \define@key{layout}{stockwidth}{\setlength\stockwidth{#1}}
131
132 \newcommand\booksize{
133     \setstocksize{\paperheight}{\paperwidth}
134     \settrimmedsize{\paperheight}{\paperwidth}{*}

```

```
135     \showtrimsoff
136 }
137 \newcommand\pbooksize{
138     \setstocksize{\stockheight}{\stockwidth}
139     \settrimmedsize{\paperheight}{\paperwidth}{*}
140     \trimcentering
141     \trimLmarks
142     \showtrimson
143 }
144
145 \define@boolkey{layout}{ebook}[true]{}
146
147 \define@key{layout}{layout}[vartwo]{
148     \ifthenelse{\equal{#1}{vartwo}}{
149         \@vartwotrue
150     }{
151         \@vartwofalse
152     }
153     \ifthenelse{\equal{#1}{none}}{
154         \@nonelayouttrue
155     }{}
156 }
157
158 \newcommand\vartwolayout{
159     \@ifpackageloaded{hoze-illust}{
160         \setfigtabjustify{\raggedright}
161     }{}
162     \vartwomargin
163     \vartwofolio
164     \renewcommand\chpalign{\raggedleft}
165 }
166
167 \newcommand\normallayout{
168     \@ifpackageloaded{hoze-illust}{
169         \setfigtabjustify{\centering}
170     }{}
171     \normalmargin
172     \normalfolio
173 }
174
175 \newcommand\setlayout{
176     \ifKV@layout@ebook
177         \ebooksize
178         \@ifpackageloaded{hyperref}{
179             \hypersetup{colorlinks=true,linkcolor=blue}
180         }{}
181     \else
182         \pbooksize
183     \fi
184     \if@nonelayout\else
```

```
185         \if@vartwo
186             \vartwolayout
187         \else
188             \normallayout
189         \fi
190     \fi
191     \if@vartwo
192         \aliaspagestyle{plain}{vartwo}
193     \else
194         \makeoddfont{plain}{}{}{\hfont\thepage}
195         \makeoddhead{plain}{}{}{}
196         \makeevenfont{plain}{}{}{\hfont\thepage}{}{}
197         \makeevenhead{plain}{}{}{}
198     \fi
199 }
200
201 \setkeys{layout}{ebook=true}
202 %\ProcessKeyvalOptions{layout}
203
204 \newcommand\ifebook[2]{\ifKV@layout@ebook#1\else#2\fi}
```

## A.2 hoze-illust.sty

```

1  \ProvidesPackage{hoze-illust}[2010/02/01 v1.00 Easier manipulation of figures & tables for %
    technical writing]
2
3  \RequirePackage{xkeyval}
4  \RequirePackage{xifthen}
5  \RequirePackage{twoopt}
6  \RequirePackage{calc}
7  \RequirePackage{relsize}
8  \RequirePackage{graphicx}
9  \RequirePackage{xcolor}
10 \RequirePackage{colortbl}
11
12 %\DeclareGraphicsExtensions{.pdf,.png,.jpg}
13 %\DeclareGraphicsRule{.pdf}{eps}{.xbb}{}
14 %\DeclareGraphicsRule{.png}{bmp}{.xbb}{}
15 %\DeclareGraphicsRule{.jpg}{bmp}{.xbb}{}
16
17 %for variant two column layout
18 \ifthenelse{\isnamedefined{if@vartwo}}{}{
19     \newboolean{@vartwo}
20     \setboolean{@vartwo}{false}
21 }
22
23 % CAPTION * * * * *
24 %\newcommand\capfont{\rmfamily\small\bfseries}
25 %\captionnamefont{\capfont}
26 %\captiontitlefont{\capfont}
27 %\captiondelim{::~}
28
29 \setlength\abovecaptionskip{.25ex plus .125ex minus .125ex}
30 \setlength\belowcaptionskip{.25ex plus .125ex minus .125ex}
31
32 \newlength\nulllength
33 \setlength\nulllength{0pt}
34
35 \newfixedcaption{\tabcaption}{table}
36 \newcommand{\tabcaptionstyle}{}
37 \newcommand{\settabcaptionstyle}[1]{\renewcommand\tabcaptionstyle{#1}}
38
39 \newfixedcaption{\figcaption}{figure}
40 \newcommand{\figcaptionstyle}{}
41 \newcommand{\setfigcaptionstyle}[1]{\renewcommand\figcaptionstyle{#1}}
42
43 \newcommand{\figjustify}{}
44 \newcommand{\setfigjustify}[1]{\renewcommand\figjustify{#1}}
45
46 \newcommand\setfigtabjustify[1]{%
47     \setfigcaptionstyle{#1}%

```

```

48     \settabcaptionstyle{#1}%
49     \setfigjustify{#1}%
50 }
51
52
53 % ILLUSTRATION * * * * *
54 \newcommand{\figscale}{1}
55 \newcommand\setfigscale[1]{\renewcommand\figscale{#1}}
56
57 \newcommand\orgscale{}
58 \newcommand\restorefigscale{\let\figscale\orgscale}
59 \newenvironment{FigScale}[1]{\setfigscale{#1}}{\restorefigscale}
60
61 \newlength\figprotrude
62
63 \newlength{\leftboxwidth}
64 \newlength{\rightboxwidth}
65 \newlength{\interwidth}
66 \setlength\interwidth{.75em}
67 \newlength{\illustwidth}
68
69 \newlength\fixedwidth
70
71 \newcommand\exlcudegraphics{%
72     \renewcommand\includegraphics[2][\@empty]{\LARGE FIGURE HERE}
73 }
74
75 % examples of \illustfigure * * * * *
76 %\def\verbfile{verb.tmp}
77 %\setverbatimfont{\ttfamily}
78 %\renewcommand\illustfig[3][\illustfigure{#1}{#2}]{\verbatiminput{\verbfile}}
79 %\setillustfigure{topspace=3ex, bottomspace=3ex}
80 %
81 %\begin{verbatimoutput}{\verbfile}
82 %\illustfig{ConnectHDMI}{
83 %\begin{verbatimoutput}{\verbfile}
84 %\illustfig[caption={blah blah}]{ConnectHDMI}{
85 %If you want to add a caption.
86 %If you don't specify anything for label,
87 %then the figure filename is also used for label.
88 %See \href{ConnectHDMI}.
89 %}
90 %\end{verbatimoutput}
91 %\input{\verbfile}
92
93 % PF stands for placefigure * * * * *
94 \newsavebox{\PFbox}
95 \newlength{\PFboxwidth}
96 \newlength{\PFboxheight}
97

```

```
98 \newlength\PFtopspace
99 \newlength\PFbottomspace
100 \newcommand\PFtopskip{\vspace{\PFtopspace}\par\noindent}
101 \newcommand\PFbottomskip{\vspace{\PFbottomspace}\par}
102
103 \newcommand\PFcaption{}
104 \newcommand\PFcaptionfont{}
105 \newcommand\PFcaptionstyle{}
106 \newcommand\PFlabel{}
107 \newcommand\PFjustify{}
108 \newcommand\PFangle{90}
109 \newcommand\PFscale{}
110
111 \newif\ifPF@float\PF@floatfalse
112 \define@boolkey{placefigure}{float}[true]{%
113     \ifKV@placefigure@float%
114         \PF@floattrue%
115     \else%
116         \PF@floatfalse%
117     \fi%
118 }
119
120 \newif\ifPF@caption\PF@captionfalse
121 \define@key{placefigure}{caption}{%
122     \PF@captiontrue%
123     \renewcommand\PFcaption{#1}%
124 }
125 \define@key{placefigure}{captionfont}{%
126     \renewcommand\PFcaptionfont{#1}%
127 }
128 \define@key{placefigure}{captionstyle}{%
129     \renewcommand\PFcaptionstyle{\captionstyle{#1}}%
130 }
131
132 \newif\ifPF@label\PF@labelfalse
133 \define@key{placefigure}{label}{%
134     \PF@labeltrue%
135     \renewcommand\PFlabel{#1}%
136 }
137
138 \define@key{placefigure}{figurejustify}{%
139     \renewcommand\PFjustify{#1}%
140 }
141
142 \define@key{placefigure}{topspace}{%
143     \setlength\PFtopspace{#1}%
144 }
145 \define@key{placefigure}{bottomspace}{%
146     \setlength\PFbottomspace{#1}%
147 }
```

```

148
149 \newif\ifPF@rotate\PF@rotatefalse
150 \define@key{placefigure}{rotate}[90]{%
151     \ifthenelse{\equal{#1}{0}}{%
152         \PF@rotatefalse%
153     }{
154         \PF@rotatetrue%
155         \renewcommand\PF@angle{#1}%
156     }
157 }
158
159 \define@key{placefigure}{scale}[1]{%
160     \renewcommand\PF@scale{#1}%
161 }
162
163 % type = figure/picture
164 % figure option is for an external figure
165 % picture option is for an internal picture like tikzpicture
166 \newif\ifPF@figure\PF@figuretrue
167 \define@key{placefigure}{type}[figure]{%
168     \ifthenelse{\equal{#1}{figure}}{%
169         \PF@figuretrue%
170     }{%
171         \PF@figurefalse%
172     }%
173 }
174
175 \newcommand\setplacefigure[1]{%
176     \presetkeys{placefigure}{#1}{}
177 }
178
179 \setplacefigure{%
180     topspace=0.75\baselineskip-\parskip,
181     bottomspace=0.75\baselineskip-\parskip,
182     float=false,
183     type=figure,
184     captionfont=\rmfamily\small\bfseries,
185     captionstyle=\figcaptionstyle,
186     figurejustify=\figjustify,
187     scale=\figscale,
188     rotate=0
189 }
190
191 \newcommand\resetplacefigure{%
192     \PF@captionfalse%
193     \PF@labelfalse%
194 }
195
196 % definition * * * * *
197 \newcommand\placefigure[2] [] {%

```

```
198 \resetplacefigure%
199 \setkeys{placefigure}{#1}%
200 \ifPF@figure%
201     \ifPF@label\else%
202         \renewcommand\PFlabel{#2}%
203     \fi%
204     \sbox{\PFbox}{\includegraphics[scale=\PFscale]{#2}}%
205     %\sbox{\PFbox}{\PFgraphics{#2}}%
206 \else%
207     \sbox{\PFbox}{#2}%
208 \fi%
209 \ifPF@float%
210     \begin{figure}[!hbt]%
211         \putPF%
212     \end{figure}%
213 \else%
214     \PFTopskip%
215     \begin{minipage}{\linewidth}%
216         \putPF%
217     \end{minipage}%
218     \PFbottomskip%
219 \fi%
220 }
221 %\newcommand\PFgraphics[1]{\includegraphics[scale=\PFscale]{#1}}
222
223 \newcommand\putPF{%
224 \ifPF@rotate%
225     \putPFlandscape%
226 \else%
227     \putPFportrait%
228 \fi%
229 }
230
231 \newcommand\putPFportrait{%
232 \if@vartwo%
233     \settowidth{\PFboxwidth}{\usebox{\PFbox}}%
234     \ifdim \PFboxwidth > \linewidth%
235         \addtolength{\PFboxwidth}{-\linewidth}%
236         \hspace*{-1\PFboxwidth}%
237     \fi%
238 \fi%
239 \PFjustify\usebox{\PFbox}%
240 \ifPF@caption%
241     \PFcaptionstyle%
242     \ifPF@float%
243         \vspace{1.25ex}\PFcaptionfont\caption{\PFcaption}\label{\PFlabel}%
244     \else%
245         \captionnamefont{\PFcaptionfont}%
246         \captiontitlefont{\PFcaptionfont}%
247         \figcaption{\PFcaption}\label{\PFlabel}%
```

```

248     \fi%
249 \fi%
250 }
251
252 \newcommand\putPFlandscape{%
253 \settowidth{\PFboxwidth}{\usebox{\PFbox}}
254 \PFjustify
255 \rotatebox{\PFangle}{%
256     \begin{minipage}{\PFboxwidth}%
257     \usebox{\PFbox}%
258     \ifPF@caption%
259         \PFcaptionstyle%
260         \ifPF@float%
261             \vspace{1.25ex}\PFcaptionfont\caption{\PFcaption}\label{\PFlabel}%
262         \else%
263             \captionnamefont{\PFcaptionfont}%
264             \captiontitlefont{\PFcaptionfont}%
265             \figcaption{\PFcaption}\label{\PFlabel}%
266         \fi%
267     \fi%
268     \end{minipage}%
269 }%
270 }
271
272 % IF stands for illustfigure * * * * *
273 % to place a figure with its text in a row
274 % e.g. \setillustfigure[frame=true, framerule=0.5pt, framesep=5pt, figureposition=right]
275 \newlength\figalignment
276 \setlength\figalignment{- .5\baselineskip}
277 \newcommand{\figalign}{\mbox{\}\[\figalignment]}
278
279 \newlength\IFtopspace
280 \newlength\IFbottomspace
281 \newcommand\IFtopskip{\vspace{\IFtopspace}\par\noindent}
282 \newcommand\IFbottomskip{\vspace{\IFbottomspace}\par}
283
284 \newsavebox{\IFbox}
285 \newlength{\IFboxwidth}
286 \newlength{\IFboxheight}
287
288 \newcommand\IFcaption{}
289 \newcommand\IFcaptionfont{}
290 \newcommand\IFcaptionstyle{}
291 \newcommand\IFlabel{}
292 \newcommand\IFstyle{}
293 \newcommand\IFjustify{\raggedleft}
294 \newcommand\IFalign{}
295 \newlength\IFfigurewidth
296 \newlength\IFscale
297 \newlength\IFprotrude

```

```
298 \newlength\IFframerule
299 \newlength\IFframesep
300 \setlength\IFframerule{.25pt}
301 \setlength\IFframesep{2.5pt}
302
303 \newif\ifIF@caption\IF@captionfalse
304 \define@key{illustfigure}{caption}{%
305     \IF@captiontrue%
306     \renewcommand\IFcaption{#1}%
307 }
308 \define@key{illustfigure}{captionfont}{%
309     \renewcommand\IFcaptionfont{#1}%
310 }
311 \define@key{illustfigure}{captionstyle}{
312     \renewcommand\IFcaptionstyle{\captionstyle{#1}}%
313 }
314 \newif\ifIF@label\IF@labelfalse
315 \define@key{illustfigure}{label}{%
316     \IF@labeltrue
317     \renewcommand\IFlabel{#1}%
318 }
319
320 \define@key{illustfigure}{textstyle}{%
321     \renewcommand\IFstyle{#1}%
322 }
323
324 \newif\ifIF@left\IF@leftfalse
325 \define@key{illustfigure}{figureposition}[left]{%
326     \ifthenelse{\equal{#1}{left}}{%
327         \IF@lefttrue%
328     }{%
329         \IF@leftfalse%
330     }%
331 }
332
333 \newif\ifIF@fixed\IF@fixedfalse % if to use a fixed width for figure
334 \define@key{illustfigure}{figurewidth}{%
335     \setlength\IFfigurewidth{#1}%
336     \ifdim \IFfigurewidth > \nulllength%
337         \IF@fixedtrue%
338     \else%
339         \IF@fixedfalse%
340     \fi%
341 }
342
343 \define@key{illustfigure}{scale}{%
344     \renewcommand\IFscale{#1}%
345 }
346
347 %\newif\ifIF@protrude\IF@protrudefalse % to disable protruding for the vartwo layout
```

```

348 %\define@boolkey{illustfigure}{protrude}[true]{%
349 %    \ifKV@illustfigure@protrude%
350 %        \IF@protrudetrue%
351 %        \setlength\IFprotrude{\figprotrude}%
352 %    \else%
353 %        \IF@protrudedefalse%
354 %        \setlength\IFprotrude{0pt}%
355 %    \fi%
356 %}
357
358 \define@boolkey{illustfigure}{protrude}[true]{%
359     \ifKV@illustfigure@protrude\else%
360         \setlength\IFprotrude{0pt}%
361     \fi%
362 }
363
364 \define@key{illustfigure}{protrudelength}{%
365     \setlength\IFprotrude{#1}%
366 }
367
368 \newif\ifIF@frame\IF@framefalse
369 \define@boolkey{illustfigure}{frame}[true]{%
370     \ifKV@illustfigure@frame%
371         \IF@frametrue%
372     \else%
373         \IF@framefalse%
374     \fi%
375 }
376 \define@key{illustfigure}{framerule}{
377     \setlength\IFframerule{#1}
378 }
379 \define@key{illustfigure}{framesep}{
380     \setlength\IFframesep{#1}
381 }
382
383
384 \define@key{illustfigure}{figurejustify}{%
385     \renewcommand\IFjustify{#1}%
386 }
387
388 \define@key{illustfigure}{align}[top]{
389     \ifthenelse{\equal{#1}{top}}{\renewcommand\IFalign{t}}{}
390     \ifthenelse{\equal{#1}{middle}}{\renewcommand\IFalign{m}}{}
391     \ifthenelse{\equal{#1}{bottom}}{\renewcommand\IFalign{b}}{}
392 }
393
394 \newif\ifIF@list\IF@listfalse
395 \define@boolkey{illustfigure}{list}[true]{%
396     \ifKV@illustfigure@list%
397         \IF@listtrue%

```

```
398         \else%
399             \IF@listfalse
400         \fi%
401     }
402
403     \define@key{illustfigure}{topspace}{%
404         \setlength\IFtopspace{#1}
405     }
406     \define@key{illustfigure}{bottomspace}{%
407         \setlength\IFbottomspace{#1}
408     }
409
410     % type = figure/picture
411     % figure option is for an external figure
412     % picture option is for an internal picture like tikzpicture
413     \newif\ifIF@figure\IF@figuretrue
414     \define@key{illustfigure}{type}[figure]{%
415         \ifthenelse{equal{#1}{figure}}{%
416             \IF@figuretrue%
417         }{%
418             \IF@figurefalse%
419         }%
420     }
421
422     \newcommand\setillustfigure[1]{%
423         \presetkeys{illustfigure}{#1}{}%
424     }
425
426     \newcommand\resetillustfigure{%
427         \IF@captionfalse%
428         \IF@labelfalse%
429     }
430
431     \setillustfigure{%
432         topspace=.35\baselineskip-\parskip,
433         bottomspace=.65\baselineskip-\parskip,
434         captionfont=\rmfamily\small\bfseries,
435         captionstyle=\figcaptionstyle,
436         textstyle=\sloppy,%\fussy
437         list=false,
438         protrude=true,
439         protrudelength=\figprotrude,
440         figureposition=left,
441         figurewidth=0pt,
442         frame=false,
443         align=top,
444         type=figure,
445         scale=\figscale
446     }
447
```

```

448 % definition * * * * *
449 \newcommand\illustfigure[3] [] {%
450 \resetillustfigure%
451 \setkeys{illustfigure}{#1}%
452 \ifIF@figure%
453     \ifIF@label\else%
454         \renewcommand\IFlabel{#2}%
455     \fi%
456     \ifthenelse{\not\equal{#2}{}}{%
457         \ifIF@frame%
458             \setlength\fbboxrule{\IFframerule}%
459             \setlength\fbboxsep{\IFframesep}%
460             \sbox{\IFbox}{\includegraphics[scale=\IFscale]{#2}}}%
461         \else%
462             \sbox{\IFbox}{\includegraphics[scale=\IFscale]{#2}}}%
463         \fi%
464     }{%
465         \sbox{\IFbox}{}%
466     }%
467 \else%
468     \sbox{\IFbox}{#2}%
469 \fi%
470 \putIF{#3}%
471 }
472
473 \newcommand\putIF[1] {%
474 \ifIF@fixed%
475     \setlength{\IFboxwidth}{\IFfigurewidth}%
476 \else%
477     \settowidth{\IFboxwidth}{\usebox{\IFbox}}%
478 \fi%
479 \ifIF@left%
480     \setlength\leftboxwidth{\IFboxwidth}%
481     \setlength{\rightboxwidth}{\illustwidth-\leftboxwidth-\interwidth}%
482 \else%
483     \setlength\rightboxwidth{\IFboxwidth}%
484     \setlength{\leftboxwidth}{\illustwidth-\rightboxwidth-\interwidth}%
485 \fi%
486 \if@vartwo
487     \ifIF@left%
488         \addtolength\rightboxwidth{\IFprotrude}%
489     \else%
490         \addtolength\leftboxwidth{\IFprotrude}%
491     \fi%
492 \fi%
493 \IFTopskip%
494 \begin{minipage}[t]{\illustwidth}%
495     \hspace*{-\IFprotrude}%
496     \begin{minipage}[\IFalign]{\leftboxwidth}%
497         \putIFleft{#1}%

```

```
498     \end{minipage}%
499         \hspace{\interwidth}%
500     \begin{minipage}[\IFalign]{\rightboxwidth}%
501         \putIFright{#1}%
502     \end{minipage}%
503 \end{minipage}%
504 \IFbottomskip%
505 }
506
507 \newcommand\putIFleft[1]{%
508 \ifIF@left%
509     \figalign\IFjustify\usebox{\IFbox}\putIFcaption%
510 \else%
511     \IFstyle\ifIF@list\vspace{-\topsep}\fi#1%
512 \fi%
513 }
514
515 \newcommand\putIFright[1]{%
516 \ifIF@left%
517     \IFstyle\ifIF@list\vspace{-\topsep}\fi#1%
518 \else%
519     \figalign\IFjustify\usebox{\IFbox}\putIFcaption%
520 \fi%
521 }
522
523 \newcommand\putIFcaption{%
524 \ifIF@caption%
525     \IFcaptionstyle%
526     \captionnamefont{\IFcaptionfont}%
527     \captiontitlefont{\IFcaptionfont}%
528     \figcaption{\IFcaption}\label{\IFlabel}%
529 \fi%
530 }
531
532 \newcommand\fixedillustfigure[3] []{%
533 \illustfigure[figurewidth=\fixedwidth, #1]{#2}{#3}%
534 }
535
536 % example
537 %\def\verbfile{verb.tmp}
538 %\setverbatimfont{\ttfamily}
539 %\newcommand\examfig[2] []{\illustfigure[#1]{#2}{\verbatiminput{\verbfile}}}
540 %\setillustfigure{topspace=3ex, bottomspace=3ex}
541 %
542 %\begin{verbatimoutput}{\verbfile}
543 %\examfig{ConnectHDMI}{
544 %What would be happen?
545 %}
546 %\end{verbatimoutput}
547 %\input{\verbfile}
```

```

548
549
550 % * * * * *
551 \newcommand\linefigscale{1}
552 %\newcommand\setlinefigscale[1]{\renewcommand\linefigscale{#1}}%
553 \newlength\linefigraise
554
555 \define@key{linefig}{scale}{%
556     \renewcommand\linefigscale{#1}%
557 }
558
559 \define@key{linefig}{raise}{%
560     \setlength\linefigraise{#1}%
561 }
562
563 \newcommand\setlinefig[1]{%
564     \presetkeys{linefig}{#1}{}%
565 }
566
567 \setlinefig{raise={-0.5ex}, scale=1}
568
569 \newcommand\linefig[2] []{%
570     \setkeys{linefig}{#1}%
571     \raisebox{\linefigraise}{\includegraphics[scale=\linefigscale]{#2}}%
572 }
573
574 %\newlength\landscapewidth%
575 %\setlength\landscapewidth{400mm}%
576
577 %\newcommand\remotefigscale{}
578 %\newcommand\panelfigscale{}
579 %\newcommand\connectfigscale{}
580 %\newcommand\setremotefigscale[1]{\renewcommand\remotefigscale{#1}}
581 %\newcommand\setpanelfigscale[1]{\renewcommand\panelfigscale{#1}}
582 %\newcommand\setconnectfigscale[1]{\renewcommand\connectfigscale{#1}}
583
584 \newcommand\figname{}
585 \newcommand\setfigname[1]{\renewcommand\figname{#1}}
586
587 % TABULAR * * * * *
588 %\renewcommand\arraystretch{1}
589
590 \definecolor{textgray}{gray}{0.4}
591 \definecolor{backgray}{gray}{0.9}
592 \definecolor{buttongray}{gray}{0.2}
593 \gdef\RowColor{backgray}
594
595 \newcounter{rowcnt}
596 \newcommand\grayrowhook{}
597 \newcommand\setgrayrowhook[1]{\renewcommand\grayrowhook{#1}}

```

```
598
599 \newcommand\grayrow{%
600     \rowcolor{\RowColor}%
601     \ifodd\therowcnt%
602         \gdef\RowColor{white}%
603     \else%
604         \gdef\RowColor{backgray}%
605     \fi%
606     \stepcounter{rowcnt}\grayrowhook%
607 }
608 \newcommand\grayheadrow{\rowcolor{backgray}}
609
610 \newcommand\startgrayrow{\setcounter{rowcnt}{0}}
611 \newcommand\startwhiterow{\setcounter{rowcnt}{-1}}
612 \newcommand\stopgrayrow{\let\grayrow\relax}
613
614 \setlength\heavyrulewidth{.75pt}
615 \setlength\lightrulewidth{.5pt}
616
617 % table
618 \newcolumntype[L]{>{\raggedright\arraybackslash}X}
619 \newcolumntype[C]{>{\centering\arraybackslash}X}
620 \newcolumntype[R]{>{\raggedleft\arraybackslash}X}
621
622 % PT stands for placetable * * * * *
623 \newsavebox{\PTbox}
624 \newlength{\PTboxwidth}
625 \newlength{\PTboxheight}
626
627 \newlength\PTtopspace
628 \newlength\PTbottomspace
629 \newcommand\PTtopskip{\vspace{\PTtopspace}\par\noindent}
630 \newcommand\PTbottomskip{\vspace{\PTbottomspace}\par}
631
632 \newcommand\PTcaption{}
633 \newcommand\PTcaptionfont{}
634 \newcommand\PTcaptionstyle{}
635 \newcommand\PTlabel{}
636 \newcommand\PTfont{}
637 \newcommand\PTstyle{}
638
639 \newif\ifPT@float\PT@floatfalse
640 \define@boolkey{placetable}{float}[true]{%
641     \ifKV@placetable@float%
642         \PT@floattrue%
643     \else%
644         \PT@floatfalse%
645     \fi%
646 }
647
```

```

648 \newif\ifPT@caption\PT@captionfalse
649 \define@key{placetable}{caption}{%
650     \PT@captiontrue%
651     \renewcommand\PTcaption{#1}%
652 }
653 \define@key{placetable}{captionfont}{%
654     \renewcommand\PTcaptionfont{#1}%
655 }
656 \define@key{placetable}{captionstyle}{%
657     \renewcommand\PTcaptionstyle{\captionstyle{#1}}%
658 }
659
660 \newif\ifPT@label\PT@labelfalse
661 \define@key{placetable}{label}{%
662     \PT@labeltrue%
663     \renewcommand\PTlabel{#1}%
664 }
665
666 \define@key{placetable}{tabularfont}{%
667     \renewcommand\PTfont{#1}%
668 }
669 \define@key{placetable}{tabularstyle}{%
670     \renewcommand\PTstyle{#1}%
671 }
672
673 \define@key{placetable}{topspace}{%
674     \setlength\PTtopspace{#1}
675 }
676 \define@key{placetable}{bottomspace}{%
677     \setlength\PTbottomspace{#1}
678 }
679
680 \newcommand\setplacetable[1]{%
681     \presetkeys{placetable}{#1}{}%
682 }
683
684 \newcommand\resetplacetable{%
685     \PT@captionfalse%
686     \PT@labelfalse%
687 }
688
689 \setplacetable{
690     topspace=\baselineskip-\parskip,
691     bottomspace=\baselineskip-\parskip,
692     float=false,
693     captionfont=\rmfamily\small\bfseries,
694     captionstyle=\tabcaptionstyle,
695     tabularfont=\sffamily\small,
696     tabularstyle=\tabcaptionstyle
697 }

```

```
698
699
700 \newcommand\placetable[2] [] {%
701 \resetplacetable
702 \setkeys{placetable}{#1}%
703 \sbox{\PTbox}{\PTfont#2}%
704 \ifPT@float%
705     \begin{table} [!hbt]%
706         \putPT%
707     \end{table}%
708 \else%
709     \PTtopskip%
710     \begin{minipage}{\linewidth}%
711         \putPT%
712     \end{minipage}%
713     \PTbottomskip%
714 \fi%
715 }
716
717 \newcommand\putPT{%
718 \if@vartwo%
719     \settowidth{\PTboxwidth}{\usebox{\PTbox}}%
720     \ifdim \PTboxwidth > \linewidth%
721         \addtolength{\PTboxwidth}{-\linewidth}%
722         \begin{adjustwidth}{-\PTboxwidth}{0pt}%
723             \putPTx%
724         \end{adjustwidth}%
725     \else%
726         \putPTx%
727     \fi%
728 \else%
729     \putPTx%
730 \fi%
731 }
732
733 \newcommand\putPTx{%
734 \ifPT@caption%
735     \PTcaptionstyle%
736     \ifPT@float%
737
738         \PTcaptionfont\caption{\PTcaption}\ifPT@label\label{\PTlabel}\fi\vspace{1.25ex}%
739     \else%
740         \captionnamefont{\PTcaptionfont}%
741         \captiontitlefont{\PTcaptionfont}%
742         \tabcaption{\PTcaption}\ifPT@label\label{\PTlabel}\fi%
743     \fi%
744 \fi%
745 \usebox{\PTbox}%
746 }
```

```

747 % IT stands for illusttable * * * * *
748 % to place a tabular with its text in a row
749 %\newlength\tabalignment
750 %\setlength\tabalignment{-.5\baselineskip}
751 %\newcommand{\tabalign}{\mbox{\}\[\tabalignment]}
752
753 \newlength\ITtopspace
754 \newlength\ITbottomspace
755 \newcommand\ITtopskip{\vspace{\ITtopspace}\par\noindent}
756 \newcommand\ITbottomskip{\vspace{\ITbottomspace}\par}
757
758 \newsavebox{\ITbox}
759 \newlength{\ITboxwidth}
760 \newlength{\ITboxheight}
761
762 \newcommand\ITcaption{}
763 \newcommand\ITcaptionfont{}
764 \newcommand\ITcaptionstyle{}
765 \newcommand\ITlabel{}
766 \newcommand\ITfont{}
767 \newcommand\ITstyle{}
768 \newcommand\ITjustify{\raggedleft}
769 \newcommand\ITalign{t}
770 \newlength\ITtablewidth
771 \newlength\ITprotrude
772
773 \newif\ifIT@caption\IT@captionfalse
774 \define@key{illusttable}{caption}{%
775     \IT@captiontrue%
776     \renewcommand\ITcaption{#1}%
777 }
778 \define@key{illusttable}{captionfont}{%
779     \renewcommand\ITcaptionfont{#1}%
780 }
781 \define@key{illusttable}{captionstyle}{
782     \renewcommand\ITcaptionstyle{\captionstyle{#1}}%
783 }
784 \newif\ifIT@label\IT@labelfalse
785 \define@key{illusttable}{label}{%
786     \IT@labeltrue
787     \renewcommand\ITlabel{#1}%
788 }
789
790 \define@key{illusttable}{tabularfont}{%
791     \renewcommand\ITfont{#1}%
792 }
793
794 \define@key{illusttable}{textstyle}{%
795     \renewcommand\ITstyle{#1}%
796 }

```

```
797
798 \newif\ifIT@left\IT@leftfalse
799 \define@key{illusttable}{tableposition}[left]{%
800     \ifthenelse{\equal{#1}{left}}{%
801         \IT@lefttrue
802     }{%
803         \IT@leftfalse
804     }%
805 }
806
807 \newif\ifIT@fixed\IT@fixedfalse
808 \define@key{illusttable}{tablewidth}{%
809     \setlength\ITtablewidth{#1}%
810     \ifdim \ITtablewidth > \nulllength%
811         \IT@fixedtrue%
812     \else%
813         \IT@fixedfalse%
814     \fi%
815 }
816
817 %\newif\ifIT@protrude\IT@protrudedefalse % to disable protruding for the vartwo layout
818 %\define@boolkey{illusttable}{protrude}[true]{%
819 %    \ifKV@illusttable@protrude%
820 %        \IT@protrudetrue%
821 %        \setlength\ITprotrude{\figprotrude}%
822 %    \else%
823 %        \IT@protrudedefalse%
824 %        \setlength\ITprotrude{0pt}%
825 %    \fi%
826 %}
827
828 \define@boolkey{illusttable}{protrude}[true]{%
829     \ifKV@illusttable@protrude\else%
830         \setlength\ITprotrude{0pt}%
831     \fi%
832 }
833
834 \define@key{illusttable}{protrudelength}{%
835     \setlength\ITprotrude{#1}%
836 }
837
838
839 \define@key{illusttable}{tablejustify}{%
840     \renewcommand\ITjustify{#1}%
841 }
842
843 \define@key{illusttable}{align}{
844     \ifthenelse{\equal{#1}{top}}{\renewcommand\ITalign{b}}{}
845     \ifthenelse{\equal{#1}{middle}}{\renewcommand\ITalign{m}}{}
846     \ifthenelse{\equal{#1}{bottom}}{\renewcommand\ITalign{t}}{}

```

```

847 }
848
849 \define@key{illusttable}{topspace}{%
850     \setlength\ITtopspace{#1}
851 }
852 \define@key{illusttable}{bottomspace}{%
853     \setlength\ITbottomspace{#1}
854 }
855
856 \newcommand\setillusttable[1]{%
857     \presetkeys{illusttable}{#1}{}%
858 }
859
860 \newcommand\resetillusttable{%
861     \IT@captionfalse%
862     \IT@labelfalse%
863 }
864
865 %\hangcaption
866 \setillusttable{
867     topspace=.35\baselineskip-\parskip,
868     bottomspace=.65\baselineskip-\parskip,
869     captionfont=\rmfamily\small\bfseries,
870     captionstyle=\tabcaptionstyle,
871     tabularfont=\sffamily\small,
872     textstyle=\sloppy,%\fussy
873     protrude=true,
874     protrudelength=\figprotrude,
875     tableposition=left,
876     tablewidth=0em,
877     align=top
878 }
879
880 \newcommand\illusttable[3][ ]{%
881 \resetillusttable%
882 \setkeys{illusttable}{#1}%
883 \sbox{\ITbox}{\ITfont#2}%
884 \putIT{#3}%
885 }
886
887 \newcommand\putIT[1]{%
888 \ifIT@fixed
889     \setlength{\ITboxwidth}{\ITtablewidth}
890 \else
891     \settoheight{\ITboxwidth}{\usebox{\ITbox}}%
892 \fi
893 \ifIT@left%
894     \setlength\leftboxwidth{\ITboxwidth}%
895     \setlength{\rightboxwidth}{\illustwidth-\leftboxwidth-\interwidth}%
896 \else%

```

```
897     \setlength\rightboxwidth{\ITboxwidth}%
898     \setlength{\leftboxwidth}{\illustwidth-\rightboxwidth-\interwidth}%
899 \fi%
900 \if@vartwo
901     \ifIT@left%
902         \addtolength\rightboxwidth{\ITprotrude}%
903     \else%
904         \addtolength\leftboxwidth{\ITprotrude}%
905     \fi%
906 \fi%
907 \ITtopskip%
908 \begin{minipage}[t]{\illustwidth}%
909     \hspace*{-\ITprotrude}%
910     \begin{minipage}[\ITalign]{\leftboxwidth}%
911         \putITleft{#1}%
912     \end{minipage}%
913     \hspace{\interwidth}%
914     \begin{minipage}[\ITalign]{\rightboxwidth}%
915         \putITright{#1}%
916     \end{minipage}%
917 \end{minipage}%
918 \ITbottomskip%
919 }
920
921 \newcommand\putITleft[1]{%
922 \ifIT@left%
923     \ITjustify\usebox{\ITbox}\putITcaption%
924 \else%
925     \ITstyle#1%
926 \fi%
927 }
928
929 \newcommand\putITright[1]{%
930 \ifIT@left%
931     \ITstyle#1%
932 \else%
933     \ITjustify\usebox{\ITbox}\putITcaption%
934 \fi%
935 }
936
937 \newcommand\putITcaption{%
938 \ifIT@caption%
939     \ITcaptionstyle%
940     \captionnamefont{\ITcaptionfont}%
941     \captiontitlefont{\ITcaptionfont}%
942     \tabcaption{\ITcaption}\label{\ITlabel}%
943 \fi%
944 }
945
946 %\newcommand\fixedillusttable[3][ ]{%
```

```
947 %\illusttable[tablewidth=\fixedwidth, #1]{#2}{#3}%
948 %}
949
950 \let\placefig\placefigure
951 \let\illustfig\illustfigure
952
953 \AtBeginDocument{
954 \let\orgscale\figscale
955 \setlength\illustwidth{\linewidth}
956 \ifthenelse{\boolean{@vartwo}}{
957     \setlength\figprotrude{\marginparwidth}
958 }{
959     \setlength\figprotrude{0pt}
960 }
961 \setlength\fixedwidth{\figprotrude}
962 }
```

### A.3 hoze-misc.sty

```

1  \ProvidesPackage{hoze-misc}[2010/02/01 v1.00 Miscellaneous macros for technical writing]
2
3  \RequirePackage{ifluatex}
4  \RequirePackage{xkeyval}
5  \RequirePackage{kvoptions}
6  \RequirePackage{xifthen}
7  \RequirePackage{calc}
8  \RequirePackage{relsize}
9  \RequirePackage{enumitem}
10 \RequirePackage{twoopt} % for submenu
11 \RequirePackage{graphicx}
12 \RequirePackage{xcolor}
13 \RequirePackage{fancybox}
14 \RequirePackage{eso-pic} % for watermark and page tab with chapter number.
15 \RequirePackage{tikz}
16
17 % DIVISION * * * * *
18 \renewcommand{\chapterrefname}{\chaptername~}
19 \renewcommand{\tablerefname}{\tablename}
20 \renewcommand{\figurerefname}{\figurename}
21
22 \maxsecnumdepth{subsection}
23 \setsecnumdepth{subsection}
24 \settocdepth{subsection}
25 \newcommand\secnewpageon{%
26     \setsechook{\ifthenelse{\equal{\value{section}}{0}}{\clearpage}}%
27 }
28 \newcommand\subsecnewpageon{%
29     \setsubsechook{\ifthenelse{\equal{\value{subsection}}{0}}{\clearpage}}%
30 }
31 \newcommand\secnewpageoff{\setsechook{}}
32 \newcommand\subsecnewpageoff{\setsubsechook{}}
33 %\define@boolkey{style}{secnewpage}[true]{}
34
35 % chapter, section & paragraph style * * * * *
36 %\setlength\footnotesep{.75\baselineskip}
37 \setSpacing{1.25} %\OnehalfSpacing = \setSpacing{1.35} at 9pt by memoir
38
39 \define@key{style}{paragraph}[boundary]{
40     \ifthenelse{\equal{#1}{indent}}{
41         \setlength{\parindent}{1em}
42     }{}
43     \ifthenelse{\equal{#1}{boundary}}{
44
45         \abnormalparskip{.25\baselineskip plus .1\baselineskip minus .1\baselineskip}
46         \setlength{\parindent}{0em}
47     }{}
48     \raggedbottom

```

```

48     \chapterstyle{hoze}
49     \sloppy%\fussy
50     \firmlists
51 }
52
53
54 \ProcessKeyvalOptions{style}
55
56 \newcommand{\nil}{\rule{0pt}{0pt}}
57 %\def\thinspace{\hskip.16667em\relax}
58
59 % chapter
60 \newcommand\chpfont{\normalfont\bfseries}
61 \newcommand\chpalign{\raggedright}
62
63 \makechapterstyle{hoze}{%
64     \renewcommand{\chapnamefont}{\chpalign\huge\chpfont}
65     \renewcommand{\chapnumfont}{\chpalign\huge\chpfont}
66     \renewcommand{\chaptitelfont}{\chpalign\Huge\chpfont}
67     \setlength{\beforechapskip}{50pt}
68     \setlength{\midchapskip}{20pt}
69     \setlength{\afterchapskip}{40pt}
70 }
71
72 % section
73 \setbeforesecskip{-2.5ex \@plus -1ex \@minus -.5ex}
74 \setaftersecskip{1.5ex \@plus .1ex}
75 \setbeforesubsecskip{-2ex \@plus -1ex \@minus -.5ex}
76 \setaftersubsecskip{1.ex \@plus .1ex}
77 \setbeforesubsubsecskip{-2.ex \@plus -1ex \@minus -.5ex}
78 \setaftersubsubsecskip{1.ex \@plus .1ex}
79
80 % appendix
81 \makechapterstyle{appendixhoze}{%
82     \renewcommand{\prechapternum}{\chapnumfont\@chapapp}
83     \renewcommand{\postchapternum}{}
84     \renewcommand{\chapternamenum}{\enskip}
85     \renewcommand\printchapternum{\chapnumfont \thechapter}
86     \setlength{\beforechapskip}{50pt}
87     \setlength{\midchapskip}{20pt}
88     \setlength{\afterchapskip}{40pt}
89 }
90
91 % header, footer and tab * * * * *
92 \newcommand\foliomarks{%
93 \renewcommand{\chaptermark}[1]{\chaptertabswitch\markboth{##1}{}}
94 \if@mainmatter
95     \renewcommand{\sectionmark}[1]{\markright{\thesection~##1}}
96 \else
97     \renewcommand{\sectionmark}[1]{\markright{##1}}

```

```
98 \fi
99 }
100 \addtodef{\frontmatter}{\foliomarks}
101 \addtodef{\mainmatter}{\foliomarks}
102
103 % colours
104 %\definecolor{PantoneCCLXXXVIIc}{cmyk}{1, 0.68, 0, 0.12} % blue 287c
105 %\color{PantoneCCLXXXVIIc}
106
107 % Language Tab
108 \newcommand\language\label{EN}
109 \newcounter{pagetabx}
110 \newcounter{pagetaby}
111 \newcounter{pagetabwidth}
112 \newcounter{pagetabheight}
113 \newcounter{pagetabysep}
114 \newcommand\pagetabcolor{}
115 \newcommand\pagetablabel{}
116 \newcommand\pagetabfont{\LARGE\sffamily\bfseries}
117
118 \define@key{pagetab}{x}{%
119     \setcounter{pagetabx}{#1}%
120 }
121
122 \define@key{pagetab}{y}{%
123     \setcounter{pagetaby}{#1}%
124 }
125
126 \define@key{pagetab}{width}{%
127     \setcounter{pagetabwidth}{#1}%
128 }
129
130 \define@key{pagetab}{height}{%
131     \setcounter{pagetabheight}{#1}%
132 }
133
134 \define@key{pagetab}{yspace}{%
135     \setcounter{pagetabysep}{#1}
136 }
137
138 \define@key{pagetab}{color}{%
139     \renewcommand\pagetabcolor{#1}%
140 }
141
142 \define@key{pagetab}{font}{%
143     \renewcommand\pagetabfont{#1}%
144 }
145
146 \newcommand\chaptertabswitch{}
147 \define@boolkey{pagetab}{on}[true]{%
```

```

148     \ifKV@pagetab@on%
149         \renewcommand\chaptertabswitch{\chaptertabx}%
150         \addtodef{\printindex}{\ClearShipoutPicture}{}%
151     \fi%
152 }
153
154 \define@boolkey{pagetab}{off}[true]{%
155     \ifKV@pagetab@off%
156         \renewcommand\chaptertabswitch{}%
157     \fi%
158 }
159
160 \newcommand\pagetab{%
161     \AddToShipoutPicture{%
162         \setlength{\unitlength}{1mm}%
163         \setlength\fbboxsep{0pt}%
164         \ifthenelse{\isodd{\number\c@page}}{%
165             \put(\thepagetabx, \thepagetaby){%
166                 \colorbox{\pagetabcolor}{%
167                     \makebox(\thepagetabwidth, \thepagetabheight){%
168                         \textcolor{white}{\pagetabfont\pagetablabel\quad}%
169                     }%
170                 }%
171             }%
172         }{}%
173     }%
174 }
175
176 \newcommand\chaptertabx{%
177     \renewcommand\pagetablabel{\thechapter}%
178     \ClearShipoutPicture%
179     \if@mainmatter%
180         \pagetab%
181         \addtocounter{pagetaby}{\thepagetabysep}%
182     \fi%
183 }
184
185 \newcommand\chaptertab[1]{%
186     \setkeys{pagetab}{#1}%
187 }
188
189 \newcommand\setchaptertab[1]{%
190     \presetkeys{pagetab}{#1}{}%
191 }
192
193
194 % the unit is mm.
195 \setchaptertab{
196     x=140,
197     y=150,

```

```
198         width=12,
199         height=8,
200         yspace=-10,
201         color=black,
202         font=\LARGE\sffamily\bfseries
203     }
204
205 %\newcommand\chaptertabon{
206 %     \setkeys{pagetab}{}%
207 %     \renewcommand\chaptertabswitch{\chaptertab}
208 %     \addtodef{\printindex}{\ClearShipoutPicture}{}
209 %     %\addtodef{\printindex}{\ClearShipoutPicture\indexfont}{}
210 %}
211 %\newcommand\chaptertaboff{
212 %     \renewcommand\chaptertabswitch{}
213 %     %\addtodef{\printindex}{\indexfont}{}
214 %}
215
216 \define@boolkey{style}{chaptertab}[true]{
217     \ifKV@style@chaptertab
218         \chaptertab{on}
219     \fi
220 }
221
222 \newcommand\langtab{
223     \renewcommand\pagetablabel{\language\label}
224 }
225
226 % watermark * * * * *
227 % usage:
228 %\watermark{x=30, y=30, angle=50, fontsize=90, color=red, text={Hoze is so hot!}}
229 %\watermark{x=50, y=100, scale=2, angle=-45, figure=Topfield}
230
231 \newif\if@watermarkfigure\@watermarkfiguretrue
232 \newcounter{watermarkx}
233 \newcounter{watermarky}
234 \definecolor{watermarkgray}{gray}{0.85}
235 \newcommand\watermarkcolor{watermarkgray}
236 \newcommand\watermarkfont{\sffamily}
237 \newcommand\watermarkfontsize{}
238 \newcommand\watermarktext{}
239 \newcommand\watermarkangle{}
240 \newcommand\watermarkfigure{}
241 \newcommand\watermarkfigurescale{}
242
243 \define@key{watermark}{x}{%
244     \setcounter{watermarkx}{#1}%
245 }
246 \define@key{watermark}{y}{%
247     \setcounter{watermarky}{#1}%
```

```

248 }
249 \define@key{watermark}{text}{%
250     \@watermarkfigurefalse%
251     \renewcommand\watermarktext{#1}%
252 }
253 \define@key{watermark}{font}{%
254     \renewcommand\watermarkfont{#1}%
255 }
256 \define@key{watermark}{fontsize}{%
257     \renewcommand\watermarkfontsize{\fontsize{#1}{10}\selectfont}%
258 }
259 \define@key{watermark}{color}{%
260     \renewcommand\watermarkcolor{#1}%
261 }
262 \define@key{watermark}{angle}{%
263     \renewcommand\watermarkangle{#1}%
264 }
265 \define@key{watermark}{figure}{%
266     \@watermarkfiguretrue%
267     \renewcommand\watermarkfigure{#1}%
268 }
269 \define@key{watermark}{scale}{%
270     \renewcommand\watermarkfigurescale{#1}%
271 }
272
273 \newcommand\setwatermark[1]{%
274     \presetkeys{watermark}{#1}{%
275     }
276
277     \setwatermark{
278         fontsize=80,
279         angle=62
280     }
281
282     \newcommand\watermark[1]{%
283         \setkeys{watermark}{#1}%
284         \if@watermarkfigure%
285             \putwatermarkfigure%
286         \else%
287             \putwatermarktext%
288         \fi%
289     }%
290
291     \newcommand\putwatermarktext{
292     \AddToShipoutPicture{%
293         \setlength{\unitlength}{1mm}%
294         \put(\thewatermarkx, \thewatermarky){%
295             \rotatebox{\watermarkangle}{%
296                 \textcolor{\watermarkcolor}{\watermarkfont\watermarkfontsize\watermarktext}%

```

```
297             }%
298         }%
299     }%
300 }
301
302 \newcommand\putwatermarkfigure{
303 \AddToShipoutPicture{%
304     \setlength{\unitlength}{1mm}%
305     \put(\thewatermarkx, \thewatermarky){%
306         \rotatebox{\watermarkangle}{%
307
308             \includegraphics[scale=\watermarkfigurescale]{\watermarkfigure}%
309         }%
310     }%
311 }
312
313 \newcommand\clearwatermark{\ClearShipoutPicture}
314
315 % For the shaded environment
316 \definecolor{shadecolor}{gray}{0.9}
317
318 % FONT & INDEX * * * * * %
319 %\RequirePackage{type1ec}
320
321 \newcommand\indexfont{\small\rmfamily}
322 \addtodef{\printindex}{\indexfont}{}
323 \setlength\indexcolsep{2.5em}
324 %\newcommand\symbolheadname{}
325 %\newcommand\numberheadname{}
326
327 %\newcommand\proper[1]{\emph{#1}\index{#1 @{\emph{#1}}}}
328 % \proper{}: put in the index
329 % \proper*{}: NOT put in the index
330 \newcommand\properfont{\itshape}
331 \newcommand\proper{\@ifstar{\propera}{\properb}}
332 \newcommand\propera[1]{\properfont#1}
333 \newcommand\properb[2][\@empty]{%
334     \propera{#2}%
335     \ifx#1\@empty%
336         \index{#2@{\properfont#2}}%
337     \else%
338         \index{#1@{\properfont#2}}%
339     \fi%
340 }
341
342
343 \newcommand\termfont{}
344 \define@key{term}{font}{%
345     \renewcommand\termfont{#1}%
```

```

346 }
347
348 \newcommand\termemphfont{}
349 \define@key{term}{emphfont}{%
350     \renewcommand\termemphfont{#1}%
351 }
352
353 \newif\ifterm@index\term@indexfalse
354 \newcommand\termindex{}
355 \define@key{term}{index}{%
356     \renewcommand\termindex{#1}%
357     \term@indextrue
358 }
359
360 \newcommand\setterm[1]{%
361     \presetkeys{term}{#1}{}%
362 }
363
364 \setterm{%
365     font={},%
366     emphfont={\itshape}%
367 }
368
369
370 \newcommand\term[2] []{%
371     \term@indexfalse%
372     \setkeys{term}{#1}%
373     {\termfont#2}%
374     \ifterm@index%
375         \index{\termindex @{\termfont#2}}%
376     \else%
377         \index{#2@{\termfont#2}}%
378     \fi%
379 }
380
381 \newcommand\termf{\@ifstar{\termfb}{\termfa}}
382
383 \newcommand\termfa[2] []{
384     \term@indexfalse%
385     \setkeys{term}{#1}%
386     {\termemphfont#2}%
387     \ifterm@index%
388         \index{\termindex @{\termemphfont#2}}%
389     \else%
390         \index{#2@{\termemphfont#2}}%
391     \fi%
392 }
393
394 \newcommand\termfb[1]{\{\termemphfont#1}}
395

```

```
396 %\newcommand\term[2][\@empty]{#2\ifx\@empty#1\index{#2}\else\index{#1@#2}\fi}
397 %\newcommand\termdef[1]{\index{#1|IndexBf}#1}
398 %\newcommand*\IndexBf[1]{\textbf{\hyperpage{#1}}}
399 % something should be done to be processed by texindy
400 %\newcommand\termdef[1]{\index{#1|hyperpagebf}#1}
401 %\newcommand*\hyperpagebf[1]{\textbf{\hyperpage{#1}}}
402 % hoze.xdy
403 %(require "lang/english/utf8-test.xdy")
404 %(define-attributes ("hyperpagebf"))
405 %(markup-locref :open "\hyperpagebf{" :close "}" :attr "hyperpagebf")
406
407 % \ui{}: NOT put in the index
408 % \ui*{}: put in the index
409 \newcommand\uifont{\sffamily}
410 \newcommand\ui{\@ifstar{\uib}{\uia}}
411 \newcommand\uia[1]{\{\uifont#1}}
412 \newcommand\uib[2][\@empty]{%
413 \uia{#2}%
414     \ifx#1\@empty%
415         \index{#2@{\uifont#2}}%
416     \else%
417         \index{#1@{\uifont#2}}%
418     \fi%
419 }
420 \newcommand\uibf[1]{\ui{\bfseries#1}}
421 \let\uii\uib
422
423 % \button{}: NOT put in the index
424 % \button*{}: put in the index
425 \newcommand\buttonfont{\uifont}
426 \newcommand\button{\@ifstar{\buttonb}{\buttona}}
427 \newcommand\buttona[1]{\{%
428     \setlength{\fboxsep}{1.2pt}%
429     \ovalbox{\relsize{-1}\buttonfont#1}%
430 }}
431 \newcommand\buttonb[2][\@empty]{%
432 \buttona{#2}
433     \ifx#1\@empty%
434         \index{#2@{\buttonfont#2}}%
435     \else%
436         \index{#1@{\buttonfont#2}}%
437     \fi%
438 }
439 %\newcommand\buttoni[1]{\button*{#1}}
440 \let\buttoni\buttonb
441 \let\btn\button
442
443 \newcommandtwoopt{\submenu}[4][\@empty][\@empty]{
444 \ifx#1\@empty%
445     \ui{#3} $$$ \ui*{#4}%
```

```

446 \else%
447     \ifx#2\@empty%
448         \ui{#1} $>$ \ui{#3} $>$ \ui*{#4}%
449     \else%
450         \ui{#1} $>$ \ui{#2} $>$ \ui{#3} $>$ \ui*{#4}%
451     \fi%
452 \fi%
453 }
454
455
\newcommand\registered{\raisebox{1ex}{\scriptsize\textcircled{\tiny \raisebox{-.15ex}{R}}}}
456
457 %\usetikzlibrary{positioning}
458
459 \newcommand\wrapnumfont{\wrapnumbf}
460 \newcommand\wrapnumbf{\bfseries}
461 \newcommand\wrapnumbase{}
462 \newlength\wrapnumwidth
463 %\newlength\wrapnumheight
464 \newlength\wrapsep
465 \setlength\wrapsep{1.5pt}
466 \newcommand\wrapbgcolor{black}
467 \newcommand\wrapfgcolor{white}
468
469 %\newcommand{\cirnum}[1]{\textcircled{\relsize{-3}\raisebox{.1ex}{#1}}}
470 \newcommand\cirnum[1]{%
471     \raisebox{-.25\baselineskip}{\abnormalparskip{0pt}
472         \tikz\node[%
473             circle, draw=\wrapfgcolor, thin, inner sep=.1\wrapsep,
474             top color=\wrapbgcolor, bottom color=\wrapbgcolor,
475             text width=\wrapnumwidth,
476             font=\wrapnumfont, text badly centered, \wrapfgcolor
477             ]{#1};%
478     }%
479 }
480
481
482 \newcommand\ovalnum[1]{%
483     \raisebox{-.15\baselineskip}{\abnormalparskip{0pt}
484         \tikz\node[%
485             rectangle, draw=\wrapfgcolor, thin, inner sep=\wrapsep,
486             rounded corners=3pt,
487             top color=\wrapbgcolor, bottom color=\wrapbgcolor,
488             text width=\wrapnumwidth,
489             font=\wrapnumfont, text badly centered, \wrapfgcolor
490             ]{#1};%
491     }%
492 }
493
494 \newcommand\recnum[1]{%

```

```

495         \raisebox{-.15\baselineskip}{\abnormalparskip{Opt}}
496         \tikz\node[%
497             rectangle, draw=\wrapfgcolor, thin, inner sep=\wrapsep,
498             top color=\wrapbgcolor, bottom color=\wrapbgcolor,
499             text width=\wrapnumwidth,
500             font=\wrapnumfont, text badly centered, \wrapfgcolor
501             ]{#1};%
502     }%
503 }
504
505 %\renewcommand\recnum[1]{%
506 %     \setlength\fbboxsep{\wrapsep}%
507 %     \colorbox{\wrapbgcolor}{%
508 %         \parbox{\wrapnumwidth}{%
509 %             \centering\textcolor{\wrapfgcolor}{\wrapnumfont#1}%
510 %         }%
511 %     }%
512 %}}
513
514 \define@key{wrapnum}{base}{%
515     \renewcommand\wrapnumbase{#1}%
516     \setwrapnumwidth%
517 }
518 \define@key{wrapnum}{font}{%
519     \renewcommand\wrapnumfont{\wrapnumbf#1}%
520     \setwrapnumwidth%
521 }
522
523 \newcommand\setwrapnumwidth{%
524     \settowidth\wrapnumwidth{\wrapnumfont\wrapnumbase}%
525 }
526
527 \define@key{wrapnum}{type}[circle]{%
528     \ifthenelse{\equal{#1}{circle}}{\let\wrapnum\cirnum}{}%
529     \ifthenelse{\equal{#1}{rectangle}}{\let\wrapnum\recnum}{}%
530     \ifthenelse{\equal{#1}{oval}}{\let\wrapnum\ovalnum}{}%
531 }
532
533 \define@key{wrapnum}{background}{%
534     \renewcommand\wrapbgcolor{#1}
535 }
536
537 \define@key{wrapnum}{foreground}{%
538     \renewcommand\wrapfgcolor{#1}
539 }
540
541 \define@key{wrapnum}{color}{%
542     \ifthenelse{\equal{#1}{white}}{%
543         \renewcommand\wrapbgcolor{white}%
544         \renewcommand\wrapfgcolor{black}%

```

```

545         \renewcommand\wrapnumbf{ }%
546     }{ }%
547     \ifthenelse{\equal{#1}{black}}{ }{%
548         \renewcommand\wrapbgcolor{black}%
549         \renewcommand\wrapfgcolor{white}%
550         \renewcommand\wrapnumbf{\bfseries}%
551     }{ }%
552 }
553
554 \define@key{wrapnum}{wrapseparate}{%
555     \setlength\wrapsep{#1}%
556 }
557
558 \newcommand\setwrapnum[1]{%
559     \setkeys{wrapnum}{#1}%
560 }
561
562 \newcommand\wrapcharhook{ }
563 \define@boolkey{wrapnum}{random}[true]{
564     \ifKV@wrapnum@random%
565         \renewcommand\wrapcharhook{\randomwrapnum}%
566     \else%
567         \renewcommand\wrapcharhook{ }%
568     \fi%
569 }%
570
571 \setwrapnum{%
572     type=rectangle,
573     base=99,
574 }
575
576 %%\wrapchar{ Daum }
577 %% luatex
578 \ifluatex
579 \RequirePackage{lcg}
580 \newcommand\randomwrapnum{%
581     \chgrand[first=0,last=2,quiet]\rand%
582     \ifcase\therand%
583         \setkeys{wrapnum}{type=circle}%
584     \or \setkeys{wrapnum}{type=rectangle}%
585     \or \setkeys{wrapnum}{type=oval}%
586     \fi%
587     \chgrand[first=0,last=1,quiet]\rand%
588     \ifcase\therand%
589         \setkeys{wrapnum}{color=black}%
590     \or \setkeys{wrapnum}{color=white}%
591     \fi%
592 }
593
594 \newcommand\wrapchar[2][ ]{%

```

```
595   \setwrapnum{#1}%
596   \@wrapchar#2|}%
597 }
598 \def\@wrapchar#1|{%
599   \directlua{%
600     local utf8 = unicode.utf8
601     str = "#1"
602     for i=1, utf8.len(str) do
603       char=utf8.sub(str, i, i)
604       if char==' ' then
605         macro = "\string\\hspace{0.5em}"
606       else
607
608         macro = "\string\\wrapcharhook\string\\wrapnum{..char..}\string\\hspace{-0.5em}"
609       end
610       tex.print(macro)
611     end
612   }%
613 }
614 \newcommand\wrapchar[2][]{%
615   \setkeys{wrapnum}{#1}%
616   \wrapnum{#2}
617 }
618 \fi
619 %% xetex & luatex
620 %\def\wrapchar#1{\wrapcharx#1|}
621 %\def\wrapcharx{\afterassignment\wrapcharxx\let\next= }
622 %\def\wrapcharxx{\ifx|\next\else\wrapnum\next\expandafter\wrapcharx\fi}
623
624 % terms list * * * * *
625 \setenumerate{topsep=\itemsep} % setting by the enumitem package
626 \setitemize{topsep=\itemsep} % setting by the enumitem package
627
628 \newcommand\termshighindex{}
629 \newlength\termslabelwidth{}
630 \newlength\termslabelsep{}
631 \newlength\termslabeloffset{}
632 \newlength\termsmarkersep{}
633 \newcommand\termslabelbase{\quad}
634 \newcommand\termslabelfont{\sffamily}
635 %\newcommand\cmdfont{\ttfamily}
636 \newcommand\termsmarker{}
637 \newcommand\termsdelim{}
638 \newcommand\termsfont{}
639 \newcommand\termsjustify{}
640 \newcommand\termsitemsep{}
641 \newcounter{termsenum}
642 \renewcommand\thetermsenum{\wrapnum{\arabic{termsenum}}}
643
```

```

644 \newif\ifterms@index\terms@indexfalse
645 \define@key{terms}{index}[true]{%
646     \ifthenelse{\equal{#1}{true}}{\terms@indextrue}{}
647     \ifthenelse{\equal{#1}{on}}{\terms@indextrue}{}
648     \ifthenelse{\equal{#1}{false}}{\terms@indexfalse}{}
649     \ifthenelse{\equal{#1}{off}}{\terms@indexfalse}{}
650 }
651
652 \newif\ifterms@highindex\terms@highindexfalse
653 \define@key{terms}{highindex}{%
654     \terms@highindextrue%
655     \renewcommand\termshighindex{#1}%
656 }
657
658 \newif\ifterms@enum\terms@enumfalse
659 \define@boolkey{terms}{enumerate}[true]{%
660     \ifKV@terms@enumerate%
661         \terms@enumtrue%
662         \renewcommand\termsmarker{\thetermsenum\hspace{\termsmarkersep}}%
663         \setkeys{terms}{labeloffset=1em}
664     \else%
665         \terms@enumfalse
666     \fi%
667 }
668
669 \define@key{terms}{enumeratelabel}{%
670     \renewcommand\thetermsenum{#1}%
671 }
672
673 \define@key{terms}{labelbase}{%
674     \renewcommand\termslabelbase{#1}%
675 }
676
677 \define@key{terms}{base}{%
678     \renewcommand\termslabelbase{#1}%
679 }
680
681 \define@key{terms}{labelfont}{%
682     \renewcommand\termslabelfont{#1}%
683 }
684
685 %\define@key{terms}{cmdfont}{%
686 %    \renewcommand\cmdfont{#1}%
687 %}
688
689 \define@key{terms}{marker}{%
690     \renewcommand\termsmarker{#1\hspace{\termsmarkersep}}%
691 }
692
693 \define@key{terms}{markerspace}{%

```

```
694     \setlength\termarkersep{#1}%
695 }
696
697 \define@key{terms}{labelspace}{%
698     \setlength\termslabelsep{#1}%
699 }
700
701 \define@key{terms}{delimiter}{%
702     \renewcommand\termsdelim{#1}%
703 }
704
705 \define@key{terms}{labeloffset}{%
706     \setlength\termslabeloffset{#1}%
707 }
708
709 \define@key{terms}{font}{%
710     \renewcommand\termsfont{#1}%
711 }
712
713 \define@key{terms}{justify}{%
714     \renewcommand\termsjustify{#1}%
715 }
716
717 \define@key{terms}{iteminterval}{%
718     \renewcommand\termsitemsep{#1}% =\firmlist, \tightlist
719 }
720
721 \newcommand\setterms[1]{%
722     \presetkeys{terms}{#1}{}%
723 }
724
725 \newcommand\resetterms{%
726     \terms@indexfalse%
727     \terms@highindexfalse%
728     \terms@enumfalse%
729 }
730
731 \setterms{
732     justify=\fussy,
733     markerspace=.5em,
734     labelspace=.5em,
735     labeloffset=0em,
736     iteminterval={}
737 }
738
739 \newenvironment{terms}[1] []{%
740 \begin{list}{}{%
741 \resetterms%
742 \setkeys{terms}{#1}%
743 \termsitemsep\termsjustify\termsfont%
```

```

744 \maketermslabel%
745 \settermsspace%
746 }}{%
747 \end{list}%
748 }
749
750 \newcommand\maketermslabel{
751     \setcounter{termsenum}{0}%
752     \renewcommand{\makelabel}[1]{%
753         \stepcounter{termsenum}%
754         {\termsmarker\termslabelfont##1}%
755         \ifterms@index%
756             \ifterms@highindex%
757                 \index{\termshighindex!\termslabelfont##1}%
758             \fi%
759             \index{##1@\termslabelfont##1}%
760         \fi%
761         \termsdelim\hfill%
762     }%
763 }
764
765 \newcommand\settermsspace{%
766 \settowidth\labelwidth{\termslabelfont\termsmarker\termslabelbase}\termsdelim}%
767 \setlength\labelsep{\termslabelsep}%
768 \setlength\leftmargin{\labelwidth+\labelsep+\termslabeloffset}%
769 %\setlength\topsep{1ex}%
770 \setlength\topsep{0.5\baselineskip-\parskip}
771 }
772
773 \renewcommand{\cmd}[1]{\cmdprint{##1}}%
774 \index{\expandafter\@gobble\string#1@\string\cmdprint{\string#1}}
775 % ? used instead of @ in the memoir class; changed to @ here
776
777 \newenvironment{cmds}[1] [] {%
778 \begin{list}{}{%
779 \resetterms%
780 \setkeys{terms}{##1}%
781 \termsitemsep\termsjustify\termsfont%
782 \makecmdslabel%
783 \settermsspace%
784 }}{%
785 \end{list}%
786 }
787
788 \newcommand\makecmdslabel{
789     \setcounter{termsenum}{0}%
790     \renewcommand{\makelabel}[1]{%
791         \stepcounter{termsenum}%
792         {\termsmarker\cmdprint{##1}}%
793 }

```

```
\ifterms@index\index{\expandafter@gobble\string##1@\string\cmdprint{\string##1}}\fi%
794         \termsdelim\hfill%
795     }%
796 }
797
798 % You should write like \item[Wöchentlich][Woehentlich] so that Wöchentlich will be %
    located in the position of Woehentlich.
799 %\def\termsindexitem{%
800 %     \let\ITEM\item%
801 %     \def\item{\@ifnextchar[\MYitem\MYAitem}%
802 %     \def\MYAitem{\ITEM}%
803 %     \def\MYitem[##1]{%
804 %         \def\templabel{##1}%
805 %         \@ifnextchar[\myXXitem\myXXitemA%
806 %     }%
807 %     \def\myXXitem[##1]{%
808 %         \ITEM[\templabel] \index{##1 @{\termslabelfont\templabel}}%
809 %     }%
810 %     \def\myXXitemA{%
811 %         \ITEM[\templabel] \index{\templabel @{\termslabelfont\templabel}}%
812 %     }%
813 %}
814
815 \let\listjustify\termsjustify
816 \let\deflist\terms
817 \let\enddeflist\endterms
818 \let\indlist\terms
819 \let\endindlist\endterms
820
821 % Note * * * * * %
822 \newlength\alertframesep
823 \newcommand\alertlabelpos{}
824 \newcommand\alertlabel{NOTE}
825 \newcommand\alertlabelfont{}
826 \newcommand\alertfont{}
827 \newcommand\alertjustify{}
828
829 \newenvironment{myshaded}{%
830 \setlength{\FrameSep}{\alertframesep}%
831 \ifnum\@listdepth>0%
832     \def\FrameCommand##1{%
833         \fboxsep=\FrameSep%
834         \hskip\@totalleftmargin%
835         \colorbox{shadecolor}{##1}%
836         \hskip-\linewidth \hskip-\@totalleftmargin \hskip\columnwidth%
837     }%
838     \MakeFramed{%
839         \advance\hsize-\width%
840         \advance\hsize \FrameSep%
841         \@totalleftmargin\z@ \linewidth=\hsize%
```

```

842     }%
843 \else%
844     \def\FrameCommand{%
845         \fboxsep=\FrameSep %
846         \colorbox{shadecolor}%
847     }%
848     \MakeFramed{%
849         \hspace=\linewidth%
850         \advance\hspace-2\FrameSep%
851         \FrameRestore%
852     }%
853 \fi%
854 }%
855 {\endMakeFramed}
856
857 \define@key{alert}{frameseparate}{%
858     \setlength\alertframesep{#1}%
859 }
860
861 \define@key{alert}{labelposition}[left]{%
862     \ifthenelse{\equal{#1}{left}}{\renewcommand\alertlabelpos{\raggedright}}{}%
863     \ifthenelse{\equal{#1}{center}}{\renewcommand\alertlabelpos{\centering}}{}%
864     \ifthenelse{\equal{#1}{right}}{\renewcommand\alertlabelpos{\raggedleft}}{}%
865 }
866
867 \define@key{alert}{label}{%
868     \renewcommand\alertlabel{#1}%
869 }
870
871 \define@key{alert}{labelfont}{%
872     \renewcommand\alertlabelfont{#1}%
873 }
874
875 \define@key{alert}{justify}{%
876     \renewcommand\alertjustify{#1}%
877 }
878
879 \define@key{alert}{font}{%
880     \renewcommand\alertfont{#1}%
881 }
882
883 \newcommand\setalert[1]{
884     \presetkeys{alert}{#1}{}
885 }
886
887 \setalert{
888     frameseparate=0.5em,
889     labelposition=left,
890     label=NOTE,
891     labelfont=\bfseries,

```

```

892         justify=\sloppy %\fussy
893     }
894
895     \newcommand\alert[2] [] {%
896     \setkeys{alert}{#1}%
897     \begin{myshaded}%
898     {\alertlabelpos\alertlabelfont\alertlabel\nopagebreak\par}%
899     \alertjustify\noindent\alertfont#2%
900     \end{myshaded}%
901     }
902
903     % Troubleshooting * * * * *
904     \newcounter{trouble}
905     \newcommand\ltsname{\Large List of Symptoms}
906     \newlistof{troublelist}{lts}{\ltsname}
907     \newlistentry{trouble}{lts}{0}
908     \def\ltsmark{} % to inactivate \markboth
909
910     \newcommand\symptom[1] {%
911     \subsubsection*{#1}%
912     \addcontentsline{lts}{trouble}{#1}%
913     }
914
915     % Proofreading
916     \newcommand\retouchcolor{red}
917     \newcommand\retouch[1]{\textcolor{\retouchcolor}{#1}}
918     \newenvironment{Retouch}{\color{\retouchcolor}}{}
919     %\newcommand\setretouchcolor[1]{\renewcommand\retouchcolor{#1}}
920     %\newcommand\setretouchon{\renewcommand\retouchcolor{red}}
921     %\newcommand\setretouchoff{\renewcommand\retouchcolor{black}}
922
923     \newif\if@secret\@secretfalse
924     \newcommand{\secret}[1]{\if@secret#1\fi}
925     \newcommand{\showsecret}{\@secrettrue}
926     \newcommand{\hideseecret}{\@secretfalse}
927
928     % font viewer
929     % written by
930     %viewttf.bat output_filename "font_name" fontsize
931     %\RequirePackage{fmtcount} %to use \Hexadecimal for \fontviewer
932     \newcommand\fontviewer[2] {%
933     %\newcounter{tohexa}
934     \font\test=#1 at #2pt % "font name" or font filename%
935     \newcount\charcountA \charcountA 0%
936     \newcount\charcountB \charcountB \XeTeXcountglyphs\test \advance\charcountB -1%
937     \newcount\charcountC \charcountC 0%
938     \def\ystrut {\vrule height 15.0pt depth 5.5pt width 0pt}%
939     \advance\vsizer 4\baselineskip%
940     \loop%
941     \advance\charcountC 1%

```

```

942 \leavevmode%
943 %\setcounter{tohexa}{\charcountA}
944 % \hbox{\hbox to 20mm{\hss\number\charcountA \Hexadecimal{tohexa}\quad}}%
945 % \hbox to 10mm{\test\XeTeXglyph\charcountA\ystrut\hss}}%
946 % }%
947 \hbox{\hbox to 20mm{\hss\number\charcountA\quad}}%
948 \hbox to 10mm{\test\XeTeXglyph\charcountA\ystrut\hss}}%
949 }%
950 \ifnum\charcountC = 5 \endgraf \charcountC 0 \fi%
951 \ifnum\charcountA < \charcountB \advance\charcountA 1%
952 \repeat%
953 }
954 % ***
955 % written by
956 %xelatex --shell-escape foo.tex
957 %\documentclass[a4paper]{memoir}
958 %\usepackage{xetexko}
959 %\usepackage{hoze-style}
960 %\begin{document}
961 %\hangulfontsvviewer
962 %\end{document}
963 \def\fontlistfile{kofontlist.txt}
964 \def\gethfnt{%
965 \read0 to \temp
966 \ifeof0
967 \let\next\relax
968 \else
969 \expandafter\gethfntx\temp,\end
970 \let\next\gethfnt
971 \fi
972 \next}
973 \def\gethfntx#1,#2\end{%
974 \ifcsname X#1X\endcsname\else
975 \expandafter\let\csname X#1X\endcsname\empty
976 \hangulfontspec{#1}#1
977 \qqquad
978 \quad{\bfseries }
979 \par
980 \fi}
981 \newcommand\hangulfontsvviewer{
982 \let\XLastResortX\empty
983 \def\{-{-}
984 \hangulmarks
985 \immediate\openin0\fontlistfile\relax
986 \ifeof0
987 \immediate\write18{fc-list :lang=ko:outline=true family|sort>\fontlistfile}
988 \immediate\openin0\fontlistfile\relax
989 \ifeof0
990 \errmessage{Please compile with '--shell-escape' option}
991 \def\abortprocess{\end{document}}

```

```
992     \expandafter\expandafter\expandafter\abortprocess
993   \fi
994 \fi
995 \endlinechar=-1
996 \gethfnt
997 \immediate\closein0
998 }
999 \endinput
1000
1001 % !TEX TS-program=xelatex
1002 % !TEX encoding=UTF-8 Unicode
1003 %
1004 %%
1005 \documentclass[amsmath]{oblivoir}
1006
1007 \usepackage{fapapersize}
1008 \usefapapersize{297mm,210mm,30mm,*,30mm,*}
1009
1010 \usepackage{xcolor}
1011 \usepackage{multido}
1012 \usepackage{arrayjob}
1013 \input random
1014 \newcount\iFnt
1015
1016 \newarray\FontName
1017 \newcounter{cntfnt}
1018 \setcounter{cntfnt}{4}%
1019 \readarray{FontName}{%
1020   & & & &%
1021 %   & & &%
1022 %   &HY L&HY B&HY M&HY &HY B&%
1023 %   HY B&HY M&HY L&HY M&HY B&HY B&%
1024 %   HY &HY M&HY L&HY M&HY &%
1025 %   HY &HY L&HY B&HY M&HY B&HY M&%
1026 %   HY B&HY M&%
1027 %   2006 & 2006 & 2006 &%
1028 %   & & &%
1029 %   & & &%
1030 %   & Bold& & Bold&%
1031 }
1032
1033 \newcommand\Test[1]{%
1034   \XXTestChaar#1|%
1035 }
1036 \def\XXTestChaar{%
1037   \afterassignment\XXOneChar\let\next=
1038 }
1039
1040 \def\XXOneChar{%
1041   \ifx|\next\else\PrintOneChar\next
```

```
1042   \expandafter\XXTestChaar\fi
1043 }
1044
1045 \newif\ifODDIT
1046 \newcommand\PrintOneChar[1]{%
1047   \ODDITfalse
1048   \setrannum{\iFnt}{1}{\thecntfnt}%
1049   \checkFontName(\iFnt)%
1050   \setrannum{\iFnt}{1}{3}% 3
1051   \ifodd\iFnt\ODDITfalse\else\ODDITtrue\fi
1052   \hangulfontspec{\cachedata}\hangulmarks
1053   \setrannum{\iFnt}{12}{50}% 12, 50
1054   \fontsize{\iFnt}{\iFnt}%
1055   \ifODDIT
1056     \fcolorbox{cyan!90}{cyan!80}{\color{white}#1}\else
1057     {\color{cyan!80}#1}%
1058   \fi\kern-.5em
1059 }
1060
1061 \parindent=0pt
1062
1063 \begin{document}
1064
1065 \pagestyle{empty}
1066
1067 \Test{ . ! . ?}
1068
1069 \end{document}
```



# Index

## A

A3landscape, 1  
A4, 1  
A4landscape, 1  
\alert, 14  
    angle, 12  
    color, 11  
    figure, 12  
    font, 11, 14  
    fontsize, 11  
    frameseparate, 14  
    justify, 14  
    labelfont, 14  
    labelposition, 14  
    off, 11  
    on, 11  
    scale, 12  
    text, 11  
    width, 11  
    x, 11  
    y, 11  
    yspace, 11  
align, 5, 8  
angle, 12

## B

base, 13  
bottomspace, 3, 5, 6, 8  
\btn, 12  
\button, 12  
\button\*, 12

## C

caption, 3, 4, 6, 7  
captionfont, 3, 4, 6, 7  
captionstyle, 3, 4, 6, 7  
chaptersub, 11  
\cirnum, 14  
\clearwatermark, 11  
cmds, 12  
color, 11

## E

ebook, 1  
\ebooksize, 1  
EmEditor, 13  
enumerate, 13  
enumeratelabel, 13  
\excludegraphics, 3

## F

figure, 12  
figurejustify, 3, 5  
figureposition, 5  
figurewidth, 5  
float, 3, 6  
font, 11, 13, 14  
fontsize, 11  
frame, 5  
framerule, 5  
framesep, 5  
frameseparate, 14

## H

highindex, 13

## I

\ifebook, 1  
\ifvartwo, 1  
\ifvartwoexpand, 1  
\illustfig, 4  
\illustfigure, 4  
    align, 5  
    bottomspace, 5  
    caption, 4  
    captionfont, 4  
    captionstyle, 4  
    figurejustify, 5  
    figureposition, 5  
    figurewidth, 5  
    frame, 5  
    framerule, 5  
    framesep, 5

- label, 5
- list, 5
- protrude, 5
- protrudelength, 5
- scale, 5
- textstyle, 5
- topspace, 5
- type, 4
- `\illusttable`, 7
  - align, 8
  - bottomspace, 8
  - caption, 7
  - captionfont, 7
  - captionstyle, 7
  - label, 8
  - protrude, 8
  - protrudelength, 8
  - tablejustify, 8
  - tableposition, 8
  - tablewidth, 8
  - tabularfont, 8
  - tabularstyle, 8
  - textstyle, 8
  - topspace, 8
- index, 13
- IP Setting, 12
- iteminterval, 13
  
- J**
- justify, 13, 14
  
- K**
- ko.TeX Live 2009, 13
  
- L**
- label, 3, 5, 6, 8
- labelbase, 13
- labelfont, 13, 14
- labeloffset, 13
- labelposition, 14
- labelspace, 13
- layout, 1
- list, 5
  
- M**
- marker, 13
- markerspace, 13
  
- N**
- Network Setting, 12
- `\normalfolio`, 1
- `\normallayout`, 1
- `\normalmargin`, 1
  
- O**
- off, 11
- on, 11
- `\ovalnum`, 14
  
- P**
- paperheight, 1
- paperwidth, 1
- paragraph, 11
- `\pbooksize`, 1
- pdftk, 13
- `\placefig`, 3
- `\placefigure`, 3
  - bottomspace, 3
  - caption, 3
  - captionfont, 3
  - captionstyle, 3
  - figurejustify, 3
  - float, 3
  - label, 3
  - rotate, 3
  - scale, 3
  - topspace, 3
  - type, 3
- `\placetable`, 6
  - bottomspace, 6
  - caption, 6
  - captionfont, 6
  - captionstyle, 6
  - float, 6
  - label, 6
  - tabularfont, 6
  - tabularstyle, 6
  - topspace, 6
- Profile, 12
- protrude, 5, 8
- protrudelength, 5, 8
  
- R**
- `\recnum`, 14
- `\restorefigscale`, 3
- rotate, 3
  
- S**
- scale, 3, 5, 12
- `\secnewpageoff`, 15
- `\secnewpageon`, 15
- `\setalert`, 14

---

`\setchapterstab`, 11  
`\setfigcaptionstyle`, 3  
`\setfigjustify`, 3  
`\setfigscale`, 3  
`\sethfont`, 1  
`\setillustfigure`, 4  
`\setillusttable`, 7  
`\setLayout`, 1  
`\setplacefigure`, 3  
`\setplacetable`, 6  
`\settabcaptionstyle`, 3  
`\setwatermark`, 11  
`\setwrapnum`, 14  
`stockheight`, 1  
`stockwidth`, 1  
`\submenu`, 12  
`\subsecnewpageoff`, 15  
`\subsecnewpageon`, 15  
Sumatra PDF, 13

**T**

`tablejustify`, 8  
`tableposition`, 8  
`tablewidth`, 8  
`tabularfont`, 6, 8  
`tabularstyle`, 6, 8  
`\term`, 12  
`\termf`, 12  
`\termf*`, 12  
`terms`, 12

- `base`, 13
- `enumerate`, 13
- `enumeratelabel`, 13
- `font`, 13
- `highindex`, 13
- `index`, 13
- `iteminterval`, 13
- `justify`, 13
- `labelbase`, 13
- `labelfont`, 13
- `labeloffset`, 13
- `labelspace`, 13
- `marker`, 13
- `markerspace`, 13

`text`, 11  
`textstyle`, 5, 8  
`topspace`, 3, 5, 6, 8  
`type`, 3, 4

**U**

`\ui`, 12

`\ui*`, 12

**V**

`\vartwofolio`, 1  
`\vartwolayout`, 1  
`\vartwomargin`, 1

**W**

`\watermark`, 11  
`width`, 11  
`\wrapchar`, 14  
`\wrapnum`, 14

**X**

`x`, 11

**Y**

`y`, 11  
`yspace`, 11